			LIGHT FIXT	URE SCHEDULE			
FIXTURE TAG	MANUFACTURER	MODEL#	LAMP	VOLTAGE/WATTAGE	INSTALLATION	DESCRIPTION	NOTES
В	ATLAS	WSPLD-40LED-4K-EB	LED	120V	WALL	SLIMPAK PRO WALL LIGHT, 40W VERSION	1,3
				40W		WITH 90 MINUTE EMERGENCY BATTERY BACKUP	
B1	ATLAS	WSPLD-60LED-4K-EB	LED	120V	WALL	SLIMPAK PRO WALL LIGHT, 60W VERSION	1,3
				60W		WITH 90 MINUTE EMERGENCY BATTERY BACKUP	
С	CONTECH LIGHTING	SQL3T-1-40K-12D1-W-X-M-BZ	LED	120V	WALL	SQUARE WALL SCONCE, DOWN ORIENTATION	1,2,3
				10W			
S3	COOPER LIGHTING	GALN-SA1A-740-U-T3-BZ-DIM	LED	120-277V	POLE	POLE MOUNTED SITE FIXTURE, TYPE 3	1,3
	SOLUTIONS			33W			
S5	COOPER LIGHTING	GALN-SA4A-740-U-5WQ-BZ-DIM	LED	120-277V	POLE	POLE MOUNTED SITE FIXTURE, TYPE 5 SQUARE WIDE	1,3
	SOLUTIONS			121W			

1. SEE SITE PHOTOMETRIC PLAN ON THIS SHEET FOR FIXTURE MOUNTING HEIGHT

2. ALTERNATE FIXTURE: CERDECO ALUMINUM MODERN OUTDOOR WALL SCONCE, 10.75", EXTERIOR DOWN ONE LIGHT, MATTE BLACK

3. VERIFY LAMP COLOR AND FINSH WITH ARCHITECT PRIOR TO ORDERING

AVERAGE: 3.1 FC MAXIMUM: 21.9 FC MINIMUM: 0.3 FC MAX/MIN: 73.0:1 AVERAGE/MIN: 10.3:1 PROPERTY BOUNDARY +<sup>2.6</sup> B +<sup>3.3</sup> 11'-0"




ARCHITECT OF RECORD: JOHN PAUL FRANK 8131 Metcalf Ave, Suite 300 Overland Park, KS 66204 www.brrarch.com Fax: 913-262-9044



This drawing was prepared for use on a specific site contemporaneously with its issue date and it is not suitable for use on a different project site or at a later time. Use of this drawing for reference or example on another project requires the services of properly licensed architects and engineers. Reproduction of this drawing for reuse on

Reproduction or this drawing for reuse on another project is not authorized and may be contrary to the law.  Ssues & Revisions						
		_				



PARKINIG AREA AND DRIVE THRU STATISTICS:







