



Commercial Lighting

Roadway Lighting

Area Lighting




Pendant Lighting

Post Top Lighting

Poles and Brackets

Roadway Lighting

ROADWAY LIGHTING

Manufacturer	Style	Fixture	Pole Options	Bracket Options	Light Pattern	Line Watts/ NEMA Label	Color Temp	Lumens	Glare Rating (BUG)	.ies File	Billing Tier
Cree	LEDWay Turtle Friendly	 (Gray)	7, 8	1	3	100/100	614nm	5,316	B2-U0-G2	PL04235-001 XSL0306D-UC4.ies	F5
	RSW	 (Gray)	7, 8	1	3	28/30	3000K	3,300	B1-U0-G1	RSWS-3ME-3L-30K7.ies	B2
			7, 8	1	3	26/30	4000K	3,300	B1-U0-G1	RSWS-3ME-3L-40K7 CONFIGURED.ies	B2
			7, 8	1	3	45/50	3000K	5,000	B1-U0-G1	RSWS-3ME-5L-30K7 CONFIGURED.ies	C2
			7, 8	1	3	41/40	4000K	5,000	B1-U0-G1	RSWS-3ME-5L-40K7 CONFIGURED.ies	C2
	XSP1-A	 (Gray)	7, 8	1	3	53/50	4000K	4,086	B1-U0-G1	BXSP-B-HT-3ME-A-40K-UL PL10397-001.ies	D3
	XSP1-D		7, 8	1	3	38/40	4000K	3,701	B1-U0-G1	BXSP-B-HT-3ME-A-40K-UL-XX-N-Q6 CONFIGURED.ies	C3
	XSP2	 (Gray)	7, 8	1	3	102/100	4000K	10,882	B2-U0-G2	BXSP-C-HT-3ME-A-40K-UL-XX-N-Q4 CONFIGURED.ies	F3
			7, 8	1	3	139/140	4000K	13,434	B2-U0-G2	BXSP-C-HT-3ME-F-30K-UL CONFIGURED.ies	H3
AEL	ATBS	 (Gray)	7, 8	1	2	40/40	4000K	4,770	B1-U0-G1	ATBS_E_XXXXX_R2.ies	C2
			7, 8	1	2	47/50	4000K	5,392	B1-U0-G1	ATBS_F_XXXXX_R2.ies	C2
			7, 8	1	2	76/80	4000K	8,653	B2-U0-G2	ATBS_I_XXXXX_R2.ies	E2
	ATBM	 (Gray)	7, 8	1	3	115/110	4000K	13,416	B3-U0-G3	ATBM_E_XXXXX_R3_XXXX.ies	G2
	ATBL	 (Gray)	7, 8	1	3	259/260	4000K	28,091	B3-U0-G4	ATBL_F_XXXXX_R3.ies	N4
	ATB2	 (Gray)	7, 8	1	4	274/270	4000K	29,567	B3-U0-G5	ATB2_80BLEDE10_XXXXX_R4.ies	O5
		 (Bronze)	7, 8	Hybrid only	4	138/140	4000K	15,015	B2-U0-G3	ATB2_40BLEDE10_XXXXX_R4.ies	H3
			7, 8	Hybrid only	4	274/270	4000K	29,567	B3-U0-G5	ATB2_80BLEDE10_XXXXX_R4.ies	O5
		 (Black)	7, 8	2	4	138/140	4000K	15,015	B2-U0-G3	ATB2_40BLEDE10_XXXXX_R4.ies	H3
			7, 8	2	4	274/270	4000K	29,567	B3-U0-G5	ATB2_80BLEDE10_XXXXX_R4.ies	O5
Cooper	Verdeon	 (Gray)	7, 8	1	3	182/180	4000K	22,236	B3-U0-G3	VERD-M-A03-E-U-T3-AP.ies	J4
	Verdeon M	 (Gray)	7, 8	1	3	247/250	4000K	29,537	B3-U0-G4	VERD-M-A04-E-U-T3-AP.ies	N4

Note: All roadway fixtures are grey unless otherwise noted

Area Lighting

AREA LIGHTING

Manufacturer	Style	Fixture	Pole Options	Bracket Options	Light Pattern	Line Watts/ NEMA Label	Color Temp	Lumens	Glare Rating (BUG)	.ies File	Billing Tier
Cooper	Galleon	 (Black)	1*	S/D	4	113W	4000K	12,336	B1-U0-G2	GAN-AF-02-LED-U-T4W.ies	G3
			1*	S/D	4	225W	4000K	23,844	B3-U0-G4	GAN-AF-04-LED-U-T4W.ies	M4
			1*	S/D	4	445W	4000K	47,372	B4-U0-G5	GAN-AF-08-LED-U-T4W.ies	T6
			1*	S/D	4	558W	4000K	58,506	B4-U0-G5	GAN-AF-10-LED-U-T4W.ies	T7
		 (Gray)	1*	S/D	4	113W	4000K	12,336	B1-U0-G2	GAN-AF-02-LED-U-T4W.ies	G3
			1*	S/D	4	225W	4000K	23,844	B3-U0-G4	GAN-AF-04-LED-U-T4W.ies	M4
			1*	S/D	4	445W	4000K	47,372	B4-U0-G5	GAN-AF-08-LED-U-T4W.ies	T6
			1*	S/D	4	558W	4000K	58,506	B4-U0-G5	GAN-AF-10-LED-U-T4W.ies	T7
		 (Bronze)	1*	S/D	4	113W	4000K	12,336	B1-U0-G2	GAN-AF-02-LED-U-T4W.ies	G3
			1*	S/D	4	225W	4000K	23,844	B3-U0-G4	GAN-AF-04-LED-U-T4W.ies	M4
			1*	S/D	4	445W	4000K	47,372	B4-U0-G5	GAN-AF-08-LED-U-T4W.ies	T6
			1*	S/D	4	558W	4000K	58,506	B4-U0-G5	GAN-AF-10-LED-U-T4W.ies	G7

S/D = Single or dual brackets.

* = 20' Standard concrete pole for 113W only.
 = 30' Standard concrete pole applicable to all.

Pendant Lighting

PENDANT LIGHTING

Manufacturer	Style	Fixture	Pole Options	Bracket Options	Light Pattern	Line Watts/ NEMA Label	Color Temp	Lumens	Glare Rating (BUG)	.ies File	Billing Tier
Holophane	Bern	 (Black)	5	3	3	70/70	4000K	5,052	B2-U3-G3	501199 GBLB 070 4K XXXX 3.ies	E10
	Domus (Memphis)	 (Black)	5	3	3	144/140	4000K	15,098	B2-U0-G3	LTL29277P14 ESL2 P35S 40K XX SG 3 DS.ies	H10
	Teardrop (Memphis)	 (Black)	5	3	3	144/140	4000K	15,375	B2-U3-G4	LTL29193P14 ESL2 P35S 40K XX TG 3.ies	H10

Post Top Lighting

POST TOP LIGHTING

Manufacturer	Style	Fixture	Pole Options	Bracket Options	Light Pattern	Line Watts/ NEMA Label	Color Temp	Lumens	Glare Rating (BUG)	.ies File	Billing Tier
AEL	Traditional Carriage (American Revolution)	 (Black)	1 (20'), 3	NA	3	39/40	3000K	2,967	B1-U3-G1	247L_10LEDE10_3K_R3_AY.ies	C2
			1 (20'), 3	NA	3	73/70	3000K	5,553	B2-U3-G2	247L_20LEDE10_3K_R3_AY.ies	E2
			1 (20'), 3	NA	3	39/40	4000K	3,187	B1-U3-G1	247L_10LEDE10_XXXX_4K_R3_AY.ies	C2
			1 (20'), 3	NA	3	73/70	4000K	5,962	B2-U3-G2	247L_20LEDE10_XXXX_4K_R3_AY.ies	E2
	Contemporary (Contempo)	 (Grey)	1 (20'), 3	NA	3	38/40	3000K	2,970	B1-U3-G1	245L_10LEDE10_XXXX_3K_R3_RNA.ies	C2
			1 (20'), 3	NA	3	72/70	3000K	5,565	B2-U3-G2	245L_20LEDE10_XXXX_3K_R3_RNA.ies	E2
			1 (20'), 3	NA	3	38/40	4000K	3,188	B1-U3-G1	245L_10LEDE10_XXXX_4K_R3_RNA.ies	C2
			1 (20'), 3	NA	3	72/70	4000K	5,977	B2-U3-G2	245L_20LEDE10_XXXX_4K_R3_RNA.ies	E2
Cooper	Mesa	 (Black)	1 (20'), 3	NA	3	75/80	4000K	7,456	B2-U0-G2	MSA-E03-LED-E1-T3.ies	E5
			1 (20'), 3	NA	3	150/150	4000K	14,911	B3-U0-G3	MSA-E06-LED-E1-T3.ies	I6
Holophane	Granville	 Black/Black	6*	NA or 4	3	39/40	3000K	4,990	B2-U3-G4	ISF 32566P8 GVD2 P20 30K AS 3 N.ies	C5
			6*	NA or 4	3	39/40	5000K	4,990	B2-U3-G4	ISF 32566P12 GVD2 P20 50K AS 3 N.ies	C5
			6*	NA or 4	3	60/60	3000K	7,076	B2-U4-G5	ISF 32566P14 GVD2 P30 30K AS 3 N.ies	D5
			6*	NA or 4	3	60/60	5000K	7,076	B2-U4-G5	ISF 32566P17 GVD2 P30 50K AS 3 N.ies	D5
	Granville	 Clear/Black	6*	NA or 4	3	60/60	5000K	7,076	B2-U4-G5	ISF 32566P17 GVD2 P30 50K AS 3 N.ies	D5
	Granville	 Green/Green	6	NA	3	39/40	3000K	4,990	B2-U3-G4	ISF 32566P8 GVD2 P20 30K AS 3 N.ies	C5
			6	NA	3	39/40	5000K	4,990	B2-U3-G4	ISF 32566P12 GVD2 P20 50K AS 3 N.ies	C5
			6	NA	3	60/60	3000K	7,076	B2-U4-G5	ISF 32566P14 GVD2 P30 30K AS 3 N.ies	D5
			6	NA	3	60/60	5000K	7,076	B2-U4-G5	ISF 32566P17 GVD2 P30 50K AS 3 N.ies	D5
	Granville w/Lunar Optics	 Silver/Clear	2, 6	NA	3	39/40	3000K	4,990	B1-U3-G1	ISF 30152P15 GVD2 P20 30K AS 6 N.ies	C5
			2, 6	NA	3	39/40	5000K	4,990	B1-U3-G1	ISF 30152P2 GVD2 P20 50K AS 6 N.ies	C5
			2, 6	NA	3	60/60	3000K	7,076	B1-U3-G2	ISF 30152P3 GVD2 P30 30K AS 6 N.ies	D5
			2, 6	NA	3	60/60	5000K	7,076	B1-U3-G2	ISF 30152P5 GVD2 P30 50K AS 6 N.ies	D5

*Also available in double bracket configuration

Poles and Brackets

POLES AND BRACKETS

Standard
Concrete



1

Tenon Mount
(20', 35')

Silver Coral Gables
Fiberglass



2

Tenon Mount
(10')

Standard Black
Fiberglass



3

Tenon Mount
(13', 20')

Coming Soon

Black Octagonal
Concrete



5

Tenon Mount
(37')

Black or Green
Washington Concrete



6

Tenon Mount
(18.5')

Standard
Wood



7

Arm Mount
(35', 40', 45')

Standard
Concrete



8

Arm Mount
(30', 35', 40', 45')

BRACKETS



1

Style

Standard
2', 6', 8'
Side Mounted

Color

Silver



2

Style

Standard
8'
Side Mounted Arm

Color

Black



3

Style

Decorative
6' Tenon Mounted
Arm or Decorative
48" Pedestrian Side
Mounted Arm

Color

Black



4

Style

Decorative
Double Bracket
Tenon Mounted Arm

Color

Black