



Tampa FL  
 8111 East Adamo Dr.  
 Tampa, FL 33619  
 800-575-7383

# Customer Proposal Letter

City of Venice  
 221 S. Seaboard Ave.  
 Venice, FL 34285  
 (941) 486-2422

Travis Hout, thank you for the opportunity to earn your business. We look forward to working with you on your business needs. Please accept the following proposal.

## VEHICLE

Make Peterbilt Model 520 Year 2020 Stock Number To Be Determined

### Additional Vehicle and Accessories Description

Florida Sheriffs Bid 18-VEH16.0 Spec #16 FSA Fees Included  
 2020 Peterbilt 520 Slide Loader 46K GVWR

Quantity	1	Total
Truck Price per Unit	\$241,526.00	\$241,526.00
F.E.T. (Factory & Dealer Paid)	\$0.00	\$0.00
Net Sales Price	\$241,526.00	\$241,526.00
Optional Extended Warranty(ies)		
State Sales Tax		
Dealer Fee		
Administration Fee		
Vehicle Inventory Tax		
Additional Taxes		
Tire Recycling Program	\$6.00	\$6.00
Battery Disposal Fee	\$4.50	\$4.50
Out of State Vehicle Fee		
Rebate(s)		
Total Sales Price (Including Rebate(s))	\$241,536.50	\$241,536.50
Trade Allowance (see DISCLAIMER Below)		\$0.00

Sales Representative		<u>Paul Canadine</u>
Purchaser	signature _____	printed name _____
	signature _____	printed name _____
Accepted by Sales Manager or General Manager	title _____	date _____
	signature _____	printed name _____

**Quote good until 7/31/2019**      **Note: The above Customer Proposal is a quotation only. Sale terms subject to approval of Sales Manager of Dealer.**

DISCLAIMER: Any order based on this Proposal subject to Customer executing Dealer's standard form Retail Purchase Order incorporating above terms. Any documentary fees, state tax, title, registration and license fees subject to adjustment and change. Actual F.E.T. to be paid by Dealer, subject to adjustment. Any F.E.T. variance will be responsibility of Dealer. Manufacturer has reserved the right to change the price to Dealer of any vehicle not currently in Dealer's stock, without notice to Dealer. If Quoted Vehicle(s) not currently in Dealer's stock, Dealer reserves right to change Quotation Total to reflect any price increases from Manufacturer. This Proposal is based upon Dealer's current and expected inventory, which is subject to change. Dealer not obligated to retain any specific vehicles in stock, nor maintain any specific inventory level. Dealer shall not be obligated to fulfill Proposal in event quoted vehicle(s) not in stock or available within requested delivery schedule at time Proposal accepted. Dealer shall not be liable for any delay in providing or inability to provide Quoted Vehicle(s), where such inability or delay is due, in whole or in part, to any cause beyond the reasonable control of Dealer or is without the gross negligence or intended misconduct of Dealer. Above listed Trade Value based upon current appraisal of Trade Vehicle(s). Dealer may adjust Trade Value of Trade Vehicle(s) to reflect changes in condition and/or mileage of Trade Vehicle(s) between date of current appraisal and acceptance of this Proposal by Customer.



www.rushtruckcenters.com

Rush Truck Center – Tampa | 8111 East Adamo Drive, Highway 60 | Tampa, Florida 33619 | 813-664-1441 Direct | 813-626-5024 Fax

Florida Sheriffs Bid 18-VEH16.0 Spec #16 FSA Fees Included  
 2019 Peterbilt 520 Side Loader 46K GVWR

<u>Option Code</u>	<u>Description</u>	<u>Contract Pricing</u>
Spec #16	Peterbilt 520 Base Price	\$ 136,333.00
601500	Double frame: full steel insert	\$ 615.00
6501090	LCF with right hand steering	\$ 1,200.00
2074406	PX9 350HP 1150 Torque	\$ (2,214.00)
7851330	Cab Tilt Air Assist	\$ 452.00
1513180	Single Axle Option	\$ (5,901.00)
4052110	Allison 3000 RDS-P	\$ (8,325.00)
2539090	Battery disconnect switch	\$ 221.00
1680460/1680470	Heavy Wall Axles / Lube Pump Pkg	\$ 986.00
1672630	Diff Lock Both Axles	\$ 1,841.00
Southern Sewer	New Way Sidewinder	\$ 116,548.00
	Body Credit	\$ (230.00)
State	Tire Recycling Fee	\$ 6.00
State	Battery Recycling	\$ 4.50
<b>Total</b>		<b>\$ 241,536.50</b>





Rush Truck Center P476  
8111 East Adamo Dr

City of Venice  
221 S. Seaboard Ave.

Tampa, Florida United States 33619  
Phone: (800) 575-7383  
Fax: (813) 626-5024  
Email:

Venice, Florida United States 34285  
Phone:  
Fax:  
Contact Email:  
Prepared for:

### Vehicle Summary

	Unit		Chassis	
Model:		Model 520	Fr Axle Load (lbs):	20000
Type:		Full Truck	Rr Axle Load (lbs)	26000
Description:		2019 520 ASL Spec Single Axle	G.C.W. (lbs):	46000
	<b>Application</b>		Road Conditions:	
Intended Serv.:		Refuse/On-Highway	Class A (Highway)	100
Commodity:		Refuse, Scrap, Recycling	Class B (Hwy/Mtn)	0
	<b>Body</b>		Class C (Off-Hwy)	0
Type:		Automated Side Loader	Class D (Off-Road)	0
Length (ft):		24	Maximum Grade:	6
Height (ft):		13.5	Wheelbase (in):	186
Max Laden Weight (lbs):		1000	Overhang (in):	75
	<b>Trailer</b>		Fr Axle to BOC (in):	0.1
No. of Trailer Axles:		0	Cab to Axle (in):	185.9
Type:			Cab to EOF (in):	260.9
Length (ft):		0	Overall Comb. Length (in):	319
Height (ft):		0.0		
Kingpin Inset (in):		0	<b>Special Req.</b>	
Corner Radius (in):		0	United States Registry	
	<b>Restrictions</b>			
Length (ft):		40		
Width (in):		102		
Height (ft):		13.5		

Approved by: \_\_\_\_\_ Date: \_\_\_\_\_

**Note: All sales are F.O.B. designated plant of manufacture.**

	Ask your dealer for a quote today, or visit our website @ <a href="http://www.paccarfinancial.com">www.paccarfinancial.com</a> .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/22/2018 11:12:22 AM	<b>Complete</b>	Model Number:	Model 520
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q31147510
Prepared by:	ID: SteveBell		Version Number:	38.02



Rush Truck Center P476  
8111 East Adamo Dr

City of Venice  
221 S. Seaboard Ave.

Tampa, Florida United States 33619  
Phone: (800) 575-7383  
Fax: (813) 626-5024  
Email:

Venice, Florida United States 34285  
Phone:  
Fax:  
Contact Email:  
Prepared for:

	Description	Weight
<b>Base Model</b>		
	<b>Model 520</b> Peterbilt's Model 520 is built to withstand the harsh demands of the refuse industry. The rugged, aluminum cab delivers best-in-class durability for increased uptime and lap seam construction on a zinc-coated steel sub-frame for corrosion resistance. Bulkhead-style doors provide years of watertight performance. This low-cab forward vehicle adds a new dimension of productivity and versatility. An industry-leading, 65-degree cab tilt enhances maintenance and serviceability. Body installation is cost effective and efficient and the center console provides convenient access to body control integration points.	16,475
	<b>Refuse, Scrap, Recycling</b>	0
	<b>Refuse/On-Highway</b> Truck or tractor which hauls refuse, recycled material, etc. Includes roll-on/roll-off container movement, as well as hauling refuse from transfer stations to, but not into, landfills.	0
	<b>Automated Side Loader</b>	0
	<b>United States Registry</b>	0
<b>Configuration</b>		
	<b>Not Applicable</b> Secondary Manufacturer	0
<b>Frame &amp; Equipment</b>		
	<b>10-3/4in Steel Rails 306-342in</b> 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	128
	<b>Full Steel Inner Liner</b>	641
	<b>Zinc Coated Anti Corrosion Treated Frame Rails</b> Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	4
	<b>FEPTO Provision 9in Bumper Extension</b> Includes 1350 Series Front Drive PTO Attachment Provision, Radiator with PTO Cut-Out in Grille, Radiator Protection Sleeve, and Bumper Extension	42
	<b>EOF Square without Xmbr</b> For use with body builder installed crossmember.	0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/22/2018 11:12:22 AM	<b>Complete</b>	Model Number:	Model 520
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q31147510
Prepared by:	ID: SteveBell		Version Number:	38.02



Description	Weight
<b>Omit Rear Mudflaps and Hangers</b>	0
<b>(2) Solid Mount Cable Hooks</b>	40
<b>Front Axle &amp; Equipment</b>	
<b>Dana Spicer D2000F 20,000 lb, 3.5 in. Drop</b> Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	0
<b>Taper Leaf Springs, Shocks 20,000 lb</b> Standard with Heavy Resistance Shocks.	0
<b>Power Steering Sheppard SD110 Dual</b> For use with 22,000 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	0
<b>PHP10 Iron PreSet PLUS Hubs</b>	84
<b>Dana Spicer 5in Drop IPO 3.5in, Front Axle</b> 5" drop (127MM) provides lower chassis suspension and profile.	0
<b>Bendix Air Cam Front Drum Brakes 16.5x6</b> Includes automatic slack adjusters & outboard mounted brake drums.	0
<b>Rear Axle &amp; Equipment</b>	
<b>Dana Spicer S26-190 26,000 lb</b> Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	-2,341
<b>PHP10 Iron PreSet PLUS Hubs</b>	0
<b>Long Stroke Parking Brakes, Drive Axle(s)</b>	0
<b>Diff Lock Rear-Rear Or Single Drive Axle</b> (Air Rocker Switch occupies the space of one gauge)	24
<b>Refuse Service Brakes, Steer And Drive Axles</b>	0
<b>Rear Brake Camshaft Reinforcement</b>	9
<b>Heavy Wall, Drive Axle(s)</b>	88

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/22/2018 11:12:22 AM	<b>Complete</b>	Model Number:	Model 520
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q31147510
Prepared by:	ID: SteveBell		Version Number:	38.02



Description	Weight
<b>SBM Valve</b> Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0
<b>Anti-Lock Braking System (ABS) 4S4M</b> ABS-6. Includes air braking system.	0
<b>Synthetic Axle Lubricant All Axles</b> Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0
<b>Bendix Air Cam Rear Drum Brakes 16.5x7</b> Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0
<b>Ratio 5.57 Rear Axle</b>	0
<b>Reycos 102CC 29,000 lb Single Drive</b>	-710

**Engine & Equipment**

<b>PACCAR PX-9 350@2000 GOV@2200 1150@1400</b>	0
Productivity (2017 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life.	
N21320 N205 68...Standard Maximum Speed Limit [LSL]	
N21330 N207 0...Expiration Distance	
N21350 P001 64...Maximum Accelerator Pedal Vehicle Speed	
N21370 P059 64...Maximum Cruise Speed	
N21400 N203 252...Reserve Speed Function Reset Distance	
N21410 N202 0...Maximum Cycle Distance	
N21420 N206 10...Maximum Active Distance	
N21430 N201 0...Reserve Speed Limit Offset	
N21440 P015 NO...Engine Protection Shutdown	
N21450 P026 NO...Gear Down Protection	
N21460 P046 1400.Max PTO Speed	
N21470 P062 NO...Cruise Control Auto Resume	
N21480 P068 NO...Auto Engine Brake in Cruise	
N21500 N209 0...Expiration Distance	
N21510 P520 YES..Enable Idle Shutdown Park Brake Set	
N21520 P030 5...Timer Setting	
N21530 P233 YES..Enable Impending Shutdown Warning	
N21540 P234 60...Timer For Impending Shutdown Warning	
N21550 P516 35...Engine Load Threshold	
N21570 P031 NO...Idle Shutdown Manual Override	
N21590 P230 YES..Enable Hot Ambient Automatic Override	

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/22/2018 11:12:22 AM	<b>Complete</b>	Model Number:	Model 520
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q31147510
Prepared by:	ID: SteveBell		Version Number:	38.02



Description	Weight
N21610 P172 40...Low Ambient Temperature Threshold N21620 P173 60...Intermediate Ambient Temperature Threshold N21630 P171 80...High Ambient Temperature Threshold	
<b>Engine Idle Shutdown Timer Disabled</b>	0
<b>Enable EIST Ambient Temp Override</b>	0
<b>Enable EIST in PTO Mode</b>	0
<b>Eff EIST NA Expiration Miles</b>	0
<b>Effective VSL Setting NA</b>	0
<b>Remote PTO And Throttle Provision</b>	0
<b>CARB Engine Idling Compliance DECLINED By</b> Dealer/Customer	0
<b>PACCAR 160 Amp Alternator, Brushed</b>	0
<b>Immersion Type Block Heater 110-120V</b> Standard location is center left hand under cab and includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	2
<b>PACCAR 12V Starter</b> N/A PACCAR MX Engines	0
<b>3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA</b> Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0
<b>Kissling Battery Disconnect Switch</b> 300 AMP; Mounted on battery box	3
<b>2-Speed Fan Clutch For Frequent Start/Stops</b>	0
<b>18.7 CFM Air Compressor</b> N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0
<b>PACCAR Fuel/Water Separator Standard Service</b> Interval	0
<b>No Fluid Heat Option for Fuel Filter</b>	0
<b>No Electric Heat Option for Fuel Filter</b>	0
<b>Engine Protection Shutdown</b> Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	0

**Unpublished options may require review/approval.**  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/22/2018 11:12:22 AM	<b>Complete</b>	Model Number:	Model 520
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q31147510
Prepared by:	ID: SteveBell		Version Number:	38.02



Description	Weight
<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in.	0
<b>Bugscreen-Removable Type Grill Mtd</b> Additional clips at bottom of bugscreen.	0
<b>Stainless Steel Grille</b>	0
<b>Heavy Duty Air Cleaner</b> Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0
<b>Exhaust Vertical LH</b> DPF/SCR LH Back of Cab Vertical (2017).	0
<b>Exhaust 90 Degree Diffuser</b>	0
<b>24in Ht, 5in Dia Chrome, Clear Coat Standpipe(s)</b>	0
<b>Transmission &amp; Equipment</b>	
<b>Allison 3000 RDS-P Transmission, Gen 5</b> Rugged Duty Series. Includes Rear Transmission Support except on MX engines, TranSynd Automatic Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation) Forward Ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65 / Reverse Ratios: DR-(5.03)	0
<b>SPL170 HD-XL Driveline, 1 Midship Bearing</b>	0
<b>Allison FuelSense 2.0 Not Desired</b>	0
<b>Omit Allison Neutral At Stop</b>	0
<b>Console Mounted Push Button Shifter</b> Allison transmissions	0
<b>Allison RDS Auto Neutral AK</b> Single steer LH or RH. Add Code 4540940 if plumbed to flip valve to actuate service brakes is desired.	0
<b>Allison MD/HD Shift Select AL</b> W/DUAL STATION CTRL	0

Unpublished options may require review/approval.  
 Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/22/2018 11:12:22 AM	<b>Complete</b>	Model Number:	Model 520
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q31147510
Prepared by:	ID: SteveBell		Version Number:	38.02





Description	Weight
<b>Allison 6-Speed Configuration, Close Ratio Gears</b> 3000 Series Transmissions	0
<b>Air &amp; Trailer Equipment</b>	
<b>Bendix AD-IS EP Air Dryer with Heater</b> And Coalescing Filter; Extended Purge	0
<b>Pull Cords All Air Tanks</b>	1
<b>Nylon Chassis Hose</b>	0
<b>Steel Painted Air Tanks</b> All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0
<b>Clear Outside Frame of All Air System Components</b> LH BOC	0
<b>Clear Outside Frame of All Air System Components</b> RH BOC	0
<b>Body Connection Harness: Heil</b>	0
<b>Route Air &amp; Electric Lines To Allow Welding</b> of sub frame to top of frame 8in forward of BOC to EOF	0
<b>Tires &amp; Wheels</b>	
<b>FF: BR 20PLY 315/80R22.5 M870</b> Diameter= 42.8 inches; SLR= 19.9 inches	0
<b>RR: BR 20PLY 315/80R22.5 M870</b>	188
<b>Code-rear Tire Qty 04</b>	0
<b>FF: Accur Stl Armor 29039PK 22.5X9.00</b> PHP10-5 Hand Holes	0
<b>RR: Accur Steel Armor 29300PK 22.5X9.00</b> PHP10-5 hand holes	128
<b>Code-rear Rim Qty 04</b>	0
<b>Fuel Tanks</b>	
<b>26 in Aluminum 70 Gallon Fuel Tank LH BOC</b> Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	11
<b>Location LH BOC Rear-Most 70 Gallon</b>	0
<b>Fuel Cooler</b> Required with single fuel tank.	0
<b>Top Of Fuel Tank 5 in Below Top Of Frame</b>	33

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/22/2018 11:12:22 AM	<b>Complete</b>	Model Number:	Model 520
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q31147510
Prepared by:	ID: SteveBell		Version Number:	38.02



Description	Weight
<b>Locate BOC Fuel Tank(s) Rearward</b> As Far As Possible	0
<b>DEF Tank Mounted LH BOC</b> Models 220 and 520 mounted LH cab fender	0
<b>Standard DEF To Fuel Ratio 2:1 Or Greater</b>	0
<b>DEF Tank 520</b>	0
<b>Battery Box &amp; Bumper</b>	
<b>Aluminum Space Saver Battery Box LH Back Of Cab</b>	-11
<b>Rubber Battery Pad In Bottom Of (1) Battery Box</b> Mat in box that holds batteries only	2
<b>Mount Space Saver Battery Box Top Of Box 8in</b> Below top of frame	0
<b>Steel Bumper Swept Back Painted</b> Requires bumper extension, includes 2front tow eyes with pins	2
<b>Notched Top Flange Of Bumper</b>	0
<b>Cab &amp; Equipment</b>	
<b>53in LCF ProBilt Cab RH Drive</b> Use with auto trans. Includes steel frames with alum and fiberglass panels, all alum doors, dual door stops, door locks, tinted safety glass thru-out, cab and door mounted entry grab handles, 65 degree hydraulic tilt, stainless steel grille, dual rear cab fenders, service module BOC (cab tilt pump, oil fill and dipstick, coolant fill and check, fluid fill and dipstick for auto trans), door mounted armrests, power windows, full insulation, rubber floor mats, ergonomic center control console, removable instrument panel, Driver Information Display, LED backlit gauges, pull down windshield sunshade, 16in steering wheel with integrated horn button, tilt/telescopic adjustable column, over-door storage, driver and passenger side cup holders, USB charging port and 12VDC charging outlet, header includes HVAC controls, rear cab corner windows, 18in bolt-on step on each side, self-canceling turn signals and Front Directional and Side Mounted Turn Signals.	0
<b>4.5 Inch Rubber Flares on Cab</b> and Wheel Well Fenders	0
<b>Peterbilt Driver Seat</b>	0
<b>Peterbilt Passenger Seat</b>	0
<b>Air Ride Driver</b>	43
<b>High Back Driver</b>	0
<b>Vinyl Driver</b>	0
<b>Non-Air Ride Passenger</b>	0
<b>Low Back Passenger</b>	0
<b>Vinyl Passenger</b>	0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/22/2018 11:12:22 AM	<b>Complete</b>	Model Number:	Model 520
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q31147510
Prepared by:	ID: SteveBell		Version Number:	38.02



Description	Weight
<b>Gray Interior Color</b> Includes ABS gray headliner & rear cab panel, gray vinyl engine tunnel cover. For LH, RH, and dual steer dual seated power windows are standard on both doors. For dual steer RH stand-up the LH window is power and the RH window is a manual sliding window.	0
<b>Adjustable Steering Column - Tilt/Telescope</b>	0
<b>Steering Wheel with Peterbilt Logo</b> Steering Wheel with embossed Peterbilt logo over horn button.	0
<b>Rear Window Back of Cab Standard Tint</b> 18.5in X 54in	0
<b>Two Piece Flat Windshield</b>	0
<b>Combo Fresh Air Heater/Air Conditioner</b> With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
<b>Mirrors SSSL Each Side Heated and Motorized</b> with Switch on Door. Right Click on option to See Picture in Product Portfolio.	-7
<b>(2) Convex 8 Inch SS Mirrors</b> Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	2
<b>(1) Air Horn 15in Painted</b> Mounted under cab.	0
<b>ConcertClass Without CD, Includes BT Phone and Audio, AM/FM, WB, USB and MP3.</b>	10
<b>Midlevel Speaker Package For Cab</b> (4) Speakers	6
<b>Bluetooth Located On Driver Side</b>	0
<b>SmartLINQ Remote Diagnostics</b> SmartLINQ is Peterbilt's proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesn't require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. SmartLINQ is standard with MX-13 engines and available on the models 587,579,567,389,367 and 365.	0
<b>Cab Tilt Pump Air Assist</b>	0
<b>Rain Gutters Over Driver and Passenger Doors</b>	8

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/22/2018 11:12:22 AM	<b>Complete</b>	Model Number:	Model 520
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q31147510
Prepared by:	ID: SteveBell		Version Number:	38.02



Description	Weight
<b>Peterbilt Pantograph Windshield Wipers</b> With intermittent feature.	0
<b>Backup Alarm Wiring To EOF</b>	0
<b>Main Transmission Oil Temperature Gauge</b> Located in Driver Information Display	0
<b>Air Restriction Indicator</b> Mounted on Exhaust Stanchion	0
<b>Warning Light Battery Disconnect, Switch Engaged</b> (Marker light) external mounted.	0
<b>Headlights Single Rectangular Halogen</b>	0
<b>(5) Light Guards On Marker Lights</b>	2
<b>(5) LED Clearance With (2) LED Marker Lights</b> Includes (5) lights mounted on roof of cab and (1) cab side marker light mounted in front of each cab door.	0
<b>None Furnished Stop/Tail/Backup Lights</b> Available with Full Truck only. Not available with Tractor.	0
<b>Daytime Running Lights</b> Required on all Canadian vehicles	0
<b>Paint</b>	
<b>(1) Color Axalta Two Stage - Cab/Hood</b> Base Coat/Clear Coat N85020 A - M9066EA BFI BLUE N85500 CAB ROOF M9066EA BFI BLUE N85200 FRAME L0001EA BLACK N85700 BUMPER L0001EA BLACK	0
<b>Options Not Subject To Discount</b>	
<b>Peterbilt Class 8 Standard Coverage</b> 1 year/100,000 Miles (160,000 km)	0
<b>PACCAR PX-9 Standard Coverage</b> 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0
<b>Chassis to Receive Extended Warranty</b> 1 Year Base Vehicle Towing - US. No Additional Extended Warranty is Required.	0
<b>Miscellaneous</b>	
<b>2017 EPA Emissions Engine</b> Warranty Only	0
<b>Presentation Created Using Featured Spec</b> For Model	0
<b>Total Weight</b>	<b>14907</b>

**Prices and Specifications Subject to Change Without Notice.**

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/22/2018 11:12:22 AM	<b>Complete</b>	Model Number:	Model 520
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q31147510
Prepared by:	ID: SteveBell		Version Number:	38.02



# Southern Sewer Equipment Sales

800-782-4134 • 772-595-6940 • FAX 772-595-9171

www.southernsewer.com "A Certified MBE Woman Owned Business"

Mr. Paul Canadine  
Rush Truck Center  
8111 East Adamo Drive  
Tampa, FL 33619  
Via email: canadinep@rushenterprises.com  
Copy: Mr. Steve Bell, email: bells@rushenterprises.com

March 25, 2019

Dear Paul,

Southern Sewer Equipment Sales appreciates the opportunity for the City of Venice to purchase a New Way Sidewinder **20 yard** refuse body to be mounted on your suitable chassis. Please review the attached equipment list.

Price for a New Way Sidewinder 31 yard refuse body.....	\$118,551.00*
City of Venice <b>20 Yard</b> Option Package:.....	(\$2,003.00)*
<b>Total Price.....</b>	<b>\$116,548.00*</b>

*\*These prices do not include any Florida Sheriffs Fees. Price does include delivery to any Florida municipality*

**Minimum Chassis Requirements:**

- 148" Usable CA
- 72" After Frame
- 46,000 lb. GVWR, *Tires must meet Florida DOT GVWR requirements*
- Automatic Transmission

Please feel free to contact Michael Fitzgerald at (772) 201-9432, if you have any questions.

Sincerely,

Jenny Mitchem  
Executive Sales Coordinator  
jm/vp

**Fort Pierce Office:**  
3409 Industrial 27<sup>th</sup> Street  
Fort Pierce, FL 34946

**Orlando Office:**  
10575 General Drive  
Orlando, FL 32824

**Miami Office:**  
8200 N.W. 58<sup>th</sup> Street  
Doral, FL 33166

## EQUIPMENT LIST

City of Venice

March 25, 2019

New Way Sidewinder  
Pack On The Go  
Multi Cycle Packer  
Twin 14.5" x 7" Clean Out Doors  
Chrome Cylinder Rods  
Side-Access Door to Hopper  
Nitro Carbonite Single Hoist Cylinder  
Sight Gauge on Reservoir Tank  
High Grade Hydraulic Fluid  
Reinforced, Frame Mounted Arm – 1,000 lb. Lift Capacity  
Heavy Duty Chains for Standard Arm  
In-Line Heavy Duty Grippers  
Sealed Roller Bearings on Packer Follower Panels  
Pre-crusher Panel  
Hopper Access Ladder  
Ergonomic In-Cab Control Panel and Joystick  
Positive Automatic Tailgate Lock  
Smooth Body Sidewall Design  
Acrylic Urethane Enamel Single Color Paint on Body  
ARM Powder Coat New Way Safety Yellow  
Rear Vision Camera System, Dual Cameras  
Back Up Alarm  
Body Ajar Alarm  
Tailgate Ajar Alarm  
Hour Meter  
"Arm Stowed" Indicator  
LED Body Lights  
Halogen Work Lights: 1 in Hopper, 1 Curbside Toward Arm  
Strobe Light Package (Mounted Upper Tailgate)  
Strobe Light, Surface Mount  
10 lb. Fire Extinguisher  
Triangle Kit  
1 Year Body, Arm & Hydraulic Warranty  
2 Year Cylinder Warranty



### ***City of Venice Option Package:***

#### **20 Cubic Yard Body Capacity**

Hot Shift PTO, Tandem Vane  
Arm Control Rocker Switches Under Seat  
Arm Cycle Counter  
Shovel/Broom Rack  
Additional 10 lb. Fire Extinguisher Mounted Street Side  
2) Clean Out Door Extensions  
Clean Out Tool

**Relocate Switches to Center Console: Interlock, Body Up/Down, Door Open/Close, & Pump Switch. Add Additional E-Stop on Left Side**