GENERAL NOTES:

CONSTRUCTION.

- ALL CONSTRUCTION TO BE IN ACCORDANCE WITH THE CITY OF VENICE LAND DEVELOPMENT REGULATIONS.
- THE CONTRACTOR SHALL RETAIN ON THE WORK SITE AT ALL TIMES COPIES OF ALL PERMITS NECESSARY FOR CONSTRUCTION.
- THE NORTH AMERICAN VERTICAL DATUM (NAVD) OF 1988 IS THE BENCHMARK DATUM FOR THIS PROJECT. CONVERSION FACTOR: NAVD 1988 + 1.11 FT = NGVD 1929.
- ALL AREAS DESIGNATED AS "PRESERVE OR CONSERVATION" TO BE CLEARLY DELINEATED PRIOR TO

GENERAL CONSTRUCTION NOTES:

- 1. THERE SHALL BE NO CHANGE OR DEVIATION FROM THESE PLANS UNLESS APPROVED BY THE ENGINEER OR CITY OF VENICE.
- 2. ALL CLEARING AND GRUBBING DEBRIS TO BE BURNED OR REMOVED FROM SITE AND IS PART OF CLEARING AND GRUBBING ITEM 3. IT IS THE INTENT OF THE OWNER THAT CERTAIN TREES BE DESIGNATED TO BE SAVED AND PROTECTED BY THE CONTRACTOR. IT IS ASSUMED THESE TREES ARE HEALTHY AND ARE EXPECTED TO BE PART OF THE LANDSCAPE DEVELOPMENT. THEREFORE, IF ANY TREE(S) DAMAGED BY CONSTRUCTION OPERATION OR BY OTHER MEANS (EXCLUDING LIGHTNING, WINDSTORM AND OTHER ACTS OF GOD) PERISHES WITHIN THE CONSTRUCTION PERIOD, IT WILL BE THE RESPONSIBILITY OF THE CONTRACTOR TO REMOVE AND DISPOSE OF THOSE TREES. NO ADDITIONAL COMPENSATION WILL BE MADE BY THE OWNER FOR THE LABOR, MATERIAL OR MACHINERY REQUIRED TO REMOVE SAID TREE(S). EXOTIC VEGETATION (E.G., MELALEUCA AND BRAZILIAN PEPPER) EXISTING WITHIN THE PROJECT AREA SHALL BE REMOVED AND PROPERLY DISPOSED OF IN AN APPROVED LANDFILL.
- WHERE EXCAVATIONS ARE IN CLOSE PROXIMITY OF TREES, THE CONTRACTOR SHALL USE EXTREME CARE IN NOT DAMAGING THE ROOT SYSTEM. NO EQUIPMENT, SUPPLIES OR VEHICLES SHALL BE STORED OR PARKED WITHIN THE DRIP LINE OF TREES TO REMAIN AND BE PRESERVED. IT WILL BE THE RESPONSIBILITY OF THE CONTRACTOR TO INFORM ALL OF HIS EMPLOYEES AND SUBCONTRACTORS OF THIS REQUIREMENT AND TO ENFORCE SAME.
- LAY SOD AROUND ALL INLETS, MITERED ENDWALLS, HEADWALLS, SWALES, LAKE SLOPES, AND TWO FEET (2') WIDE STRIP ADJACENT TO ALL CURBING, AND AS DIRECTED BY THE ENGINEER. ALL PROPOSED GROUND ELEVATIONS ARE FINISHED SOD ELEVATIONS. FINISH EARTHWORK GRADING WILL BE 0.2 FEET BELOW ELEVATIONS SHOWN TO ALLOW FOR SOD THICKNESS. SODDING INCLUDES MAINTAINING SLOPES AND SOD UNTIL COMPLETION AND ACCEPTANCE OF TOTAL PROJECT OR GROWTH IS ESTABLISHED WHICHEVER COMES LAST. ALL EROSION SILTATION AND MAINTAINING GRADES IS THE RESPONSIBILITY OF THE CONTRACTOR UNTIL THEN.
- CALL "SUNSHINE" (1-800-432-4770), COMCAST, FPL, CITY OF VENICE UTILITIES DEPARTMENT, TECO, AND FRONTIER PRIOR TO CONSTRUCTION AND CONNECTION TO EXISTING UTILITIES. IT IS THE CONTRACTOR'S RESPONSIBILITY TO PROTECT. EXISTING UTILITIES FROM DAMAGE.
- ALL UTILITY LINES, STORM DRAIN LINES AND ACCESSORIES SUCH AS, BUT NOT LIMITED TO MANHOLES, CLEANOUTS, SEWER AND WATER SERVICES, VALVES, FIRE HYDRANTS AND INLETS WILL BE CONSTRUCTED TO ALIGNMENT AND LOCATIONS SHOWN ON PLANS UNLESS OTHERWISE DIRECTED BY THE ENGINEER.
- 8. CLEARING, GRUBBING, STRIPPING, AND COMPACTION WILL BE INSPECTED BY THE ENGINEER PRIOR TO FILLING.
- PRIOR TO THE START OF CONSTRUCTION ACTIVITIES. CONSERVATION/PRESERVE AREAS. EXISTING LAKES & WATERWAYS WITHIN AND ADJOINING THE AREA OF CONSTRUCTION ACTIVITY SHALL BE PROTECTED BY ERECTION OF TREE PROTECTION BARRICADES AND/OR SILT BARRIERS, TREE PROTECTION BARRICADES SHALL MEET THE STANDARDS OF THE CITY OF VENICE. SILT BARRIERS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE "BEST MANAGEMENT PRACTICES PLAN" AND THE "BMP DETAILS" SHOWN ON DWGS. B-1 THROUGH B-2 OF THE FULL CIVIL CONSTRUCTION PLANS. THE ENGINEER WILL DETERMINE THE EXTENT AND TYPE OF PROTECTIVE MEASURES TO BE CONSTRUCTED FOR PROTECTION OF CONSERVATION/PRESERVE AREAS, THE ENGINEER SHALL BE NOTIFIED WHEN PRESERVE AREA BARRICADES AND BARRIERS ARE IN PLACE
- 10. THE SITE CONSTRUCTION STAKEOUT SHALL BE PERFORMED UNDER THE DIRECTION OF A FLORIDA REGISTERED SURVEYOR. AUTOCAD FILES WILL BE FURNISHED TO AID IN THE SITE CONSTRUCTION STAKEOUT. ANY DISCREPANCIES FOUND BETWEEN THE AUTOCAD FILES AND SITE CONSTRUCTION PLANS SHALL BE BROUGHT TO THE ENGINEER'S ATTENTION FOR CLARIFICATION PRIOR TO THAT STAKEOUT.
- 11. ALL DRAINAGE PIPE JOINTS SHALL BE WRAPPED PER FDOT INDEX NO. 280, SHEET 1
- 12. ROADWAY AND DRAINAGE STRUCTURES SHALL MEET FDOT STANDARD SPECIFICATIONS SECTION 346 OF 3000 PSI CONCRETE.
- 13. THE WETLAND AND ASSOCIATED UPLAND VEGETATIVE BUFFER SHALL BE MAINTAINED IN ACCORDANCE WITH MANAGEMENT GUIDELINES CONTAINED WITHIN THE COMPREHENSIVE PLAN AS A CONSERVATION AREA OR PRESERVE. ALL ACTIVITIES INVOLVING FILLING, EXCAVATING, WELL DRILLING, ALTERING VEGETATION (INCLUDING TRIMMING OF BOTH TREES AND UNDERSTORY) AND STORING OF MATERIALS SHALL BE PROHIBITED WITHIN PRESERVATION AREAS, UNLESS WRITTEN APPROVAL IS FIRST OBTAINED FROM RESOURCE PROTECTION SERVICES TO FACILITATE IMPLEMENTATION OF APPROVED HABITAT MANAGEMENT PLANS OR THE REMOVAL OF NUISANCE/INVASIVE VEGETATION.
- 14. A TREE REMOVAL AND PROTECTION PERMIT WILL BE REQUIRED PRIOR TO ANY CONSTRUCTION, CLEARING OR TREE REMOVAL. ALL WORK PERFORMED SHALL BE IN ACCORDANCE WITH THE CITY OF VENICE CODE.
- 15. EROSION AND SEDIMENT CONTROL BMPS IN ADDITION TO THOSE PRESENTED ON THE PLANS AND OUTLINED IN THE EROSION AND SEDIMENT CONTROL PLAN (ECP), BEST MANAGEMENT PRACTICES (BMP) PLAN, OR STORMWATER POLLUTION PREVENTION PLAN (SWPPP) SHALL BE IMPLEMENTED AS NECESSARY TO PREVENT TURBID DISCHARGES FROM FLOWING ONTO ADJACENT PROPERTIES OR ROADWAYS, OFF SITE STORMWATER CONVEYANCES OR RECEIVING WATERS, OR ON SITE WETLANDS AND SURFACE WATERS, BMPS SHALL BE DESIGNED, INSTALLED, AND MAINTAINED BY THE SITE OPERATOR TO ENSURE THAT OFF SITE SURFACE WATER QUALITY REMAINS CONSISTENT WITH STATE AND LOCAL REGULATIONS. ITHE OPERATOR IS THE ENTITY THAT OWNS OR OPERATES THE CONSTRUCTION ACTIVITY AND HAS AUTHORITY TO CONTROL THOSE ACTIVITIES AT THE PROJECT NECESSARY TO ENSURE COMPLIANCE.]
- OFFSITE SURFACE WATER DISCHARGES, DISCHARGES TO THE MS4, OR DISCHARGES TO ONSITE WETLANDS OR SURFACE WATERS WITH TURBIDITY IN EXCESS OF 29 NEPHELOMETRIC TURBIDITY UNITS (NTUS) ABOVE BACKGROUND LEVEL SHALL BE IMMEDIATELY CORRECTED. SUCH INCIDENTS SHALL BE REPORTED TO THE CITY OF VENICE WITHIN 24 HOURS OF THE OCCURRENCE. THE REPORT SHALL INCLUDE THE CAUSE OF THE DISCHARGE AND CORRECTIVE ACTIONS TAKEN.
- 17. FUEL AND OTHER PETROLEUM PRODUCT SPILLS THAT ENTER STORMWATER DRAINS OR WATERBODIES, OR FUEL AND OTHER PETROLEUM PRODUCT SPILLS THAT ARE IN EXCESS OF 25 GALLONS SHALL BE CONTAINED, CLEANED UP, AND IMMEDIATELY REPORTED TO THE CITY OF VENICE. SMALLER GROUND SURFACE SPILLS SHALL BE CLEANED UP AS SOON AS PRACTICAL.
- IF CONTAMINATED SOIL AND/OR GROUNDWATER IS DISCOVERED DURING DEVELOPMENT OF THE SITE, ALL ACTIVITY IN THE VICINITY OF THE CONTAMINATION SHALL IMMEDIATELY CEASE, AND THE CITY OF VENICE SHALL BE CONTACTED.
- 19. FERTILIZER APPLICATION SHALL BE CONSISTENT WITH THE CITY OF VENICE CODE
- 20. NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM STORMWATER:
 - i. NPDES CONSTRUCTION GENERIC PERMIT COVERAGE SHALL BE OBTAINED AT LEAST 48 HOURS IN ADVANCE OF CONSTRUCTION COMMENCEMENT IN ACCORDANCE WITH RULE 62-621.300(4)(A), F.A.C.
- ii. A COPY OF THE CERTIFIED NPDES NOI, OR A COPY OF THE FDEP COVERAGE CONFIRMATION LETTER SHALL BE POSTED AT THE SITE IN ACCORDANCE WITH RULE 62-621.300(4)(A)PART III.C.2. F.A.C.
- iii. A COPY OF THE CERTIFIED NPDES NOI, OR A COPY OF THE FDEP COVERAGE CONFIRMATION LETTER SHALL BE PROVIDED TO AIR AND WATER QUALITY IN ACCORDANCE WITH RULE 62-621.300(4)(A)PART III.D.1, F.A.C..
- iv. THE SWPPP SHALL BE CERTIFIED IN ACCORDANCE WITH RULE 62-621.300(4)(A)PART V.D.6, F.A.C., AND A COPY OF THE CERTIFIED DOCUMENT SHALL BE SUBMITTED TO AIR AND WATER QUALITY AT LEAST 48 HOURS PRIOR TO THE COMMENCEMENT OF CONSTRUCTION.
- v. A COPY OF THE SWPPP, AND COPIES OF THE INSPECTION AND MAINTENANCE RECORDS SHALL BE MAINTAINED AT THE PROJECT SITE, AND SHALL BE READILY AVAILABLE TO STATE INSPECTORS.
- vi. NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM DEWATERING: THE DISCHARGE OF GROUNDWATER PRODUCED THROUGH DEWATERING, TO SURFACE WATERS, OR TO ANY PORTION OF THE MS4 WILL REQUIRE SEPARATE PERMITTING FROM THE DEP. PERMIT(S) SHALL BE OBTAINED PRIOR TO THE COMMENCEMENT OF DEWATERING. ANALYTICAL RESULTS FROM PRE-DISCHARGE TESTING SHALL BE PROVIDED TO AIR AND WATER QUALITY
- 21. THE CONTRACTOR SHALL ENSURE THAT ADJACENT PROPERTIES ARE NOT IMPACTED BY WIND EROSION OR EMISSIONS OF UNCONFINED PARTICULATE MATTER IN ACCORDANCE WITH RULE 62-296.320(4)(c)1., FLORIDA ADMINISTRATIVE CODE, FROM THE CONSTRUCTION SITE BY TAKING ADEQUATE MEASURES TO STABILIZE AFFECTED AREAS.
- 22. DEPARTMENT OF ENVIRONMENTAL PROTECTION WATER AND WASTEWATER PERMITS ARE REQUIRED.
- 23. ANY WELLS DISCOVERED ON SITE THAT WILL HAVE NO USE MUST BE PLUGGED BY A LICENSED WELL DRILLING CONTRACTOR IN AN APPROVED MANNER.
- 24. IN THE EVENT THAT THE CONSTRUCTION SITE IS ABANDONED PRIOR TO THE PROJECT COMPLETION, ALL CONSTRUCTION AND VEGETATIVE DEBRIS SHALL BE REMOVED FROM THE SITE AND DISPOSED OF AT AN APPROVED LANDFILL FACILITY.
- 25. A SEPARATE BUILDING PERMIT MUST BE APPLIED FOR AND ISSUED FOR EVERY SIGN, WALL, OUTDOOR LIGHTING AND STRUCTURE ON THE SITE. THE APPROVAL OF THESE CONSTRUCTION PLANS DOES NOT EXEMPT THE CONTRACTOR FROM OBTAINING THE NECESSARY BUILDING PERMITS.


CITY OF VENICE REQUIRED NOTES:

- 1. ALL WORK CONDUCTED IN THE CITY OF VENICE RIGHT-OF-WAY (ROW) WILL REQUIRE THE ISSUANCE OF A ROW
- 2. ALL WORK CONDUCTED IN SARASOTA COUNTY AND/OR FDOT ROW SHALL REQUIRE A COPY OF STATE ISSUED
- 3. TREE REMOVAL PERMIT MUST BE OBTAINED FROM THE CITY OF VENICE.

PERMITS.

- 4. POST DEVELOPMENT RUNOFF DOES NOT EXCEED PRE-DEVELOPMENT RUNOFF VOLUME OR RATE FOR A 24-HOUR, 25-YEAR STORM EVENT.
- ALL FIRE SERVICE BACKFLOW ASSEMBLIES SHALL BE INSTALLED BY A CERTIFIED CONTRACTOR WITH A CLASS I,
- II, OR V CERTIFICATE OF COMPETENCY ISSUED BY THE STATE FIRE MARSHALL AS PER F.S. 633.521. 6. CONSTRUCTION SITE MUST BE POSTED WITH 24-HOUR CONTACT INFORMATION.
- 7. ALL UTILITIES, WHETHER PUBLIC OR PRIVATE, SHALL MEET CITY OF VENICE STANDARDS.
- 8. CONTACT PUBLIC WORKS SOLID WASTE DIVISION (941-486-2422) FOR APPROVAL OF DUMPSTER LOCATION AND LAYOUT PRIOR TO CONSTRUCTION.





PROJECT LOCATION

ATLANTA, GA 30327 PH:(404)400-1322 CONTACT: BRYAN BELLISSIMO

ENGINEER:

KIMLEY HORN AND ASSOCIATES, INC. 1777 MAIN STREET, SUITE 200 SARASOTA, FL 34236 PH :(941)379-7600 CONTACT: WILLIAM E. CONERLY, P.E.

SURVEYOR : BRITT SURVEYING, INC. 680 U.S. BYPASS N, UNIT 1 **VENICE**, FL 34285 PH : (941)493-1396 CONTACT: RANDALL E. BRITT, P.L.S.



SITE AND DEVELOPMENT PLANS FOR **RANCH ROAD MULTI-FAMILY**

SECTION 20, TOWNSHIP 38 S, RANGE 19 E NORTH VENICE, FLORIDA

JULY 2022

3715 NORTHSIDE PKWY, SUITE 1-310

DEVELOPER: SOUTH CITY PARTNERS, LLC ARCHITECT: DYNAMIK DESIGN 5901 PEACHTREE DUNWOODY ROAD. BUILDING C, SUITE 250 ATLANTA, GA 30328 (678) 506-8830 CONTACT: RUSSELL SIGMAN, AIA

> LANDSCAPE ARCHITECT: B+C STUDIO, INC. 1320 ELLSWORTH INDUSTRIAL BLVD NW, SUITE A1400, ATLANTA, GA 30318 (678) 990-7691

CONTACT: TRAE ADAMS

REQUIRED APPROVALS:

 SITE AND DEVELOPMENT PLAN APPROVAL SPECIAL EXCEPTION - FOR MODIFICATION TO PARKING STANDARDS CONDITIONAL USE - FOR BUILDING HEIGHT IN EXCESS OF 42 FEET.

GENERAL INFORMATION STATEMENTS FOR SITE AND DEVELOPMENT PLANS:

- SUBSEQUENT PERMITS REQUIRED: SITE AND DEVELOPMENT PLAN APPROVAL DOES NOT AUTHORIZE THE DEVELOPMENT OF LAND. ALL CONSTRUCTION ACTIVITIES ARE REQUIRED TO OBTAIN ANY/ALL NECESSARY PERMITS AND APPROVALS AUTHORIZING SUCH ACTIVITIES. ALL CONSTRUCTION SHALL BE CONSISTENT WITH THE APPROVED SITE AND DEVELOPMENT PLAN. PLEASE ENSURE TO OBTAIN NECESSARY PERMITS, INCLUDING BUT NOT LIMITED TO:
- BUSINESS TAX RECEIPT BUILDING PERMITS THROUGH THE BUILDING DEPARTMENT, ••
- SITE PREPARATION PERMITS(S) AND CONSTRUCTION PLAN REVIEW THROUGH THE CITY'S .. ENGINEERING DEPARTMENT AND RIGHT-OF-WAY PERMITS FOR ALL CONNECTIONS TO COUNTY FACILITIES THROUGH SARASOTA COUNTY
- PROJECT CONSTRUCTION: THE PROJECT ENGINEER OR AGENT FOR THE OWNER IS REQUIRED TO MAINTAIN CONSISTENCY WITH ALL APPROVED PLANS AND PERMITS THROUGH THE DURATION OF THE PROJECT'S CONSTRUCTION. NOTE: CHANGES DURING CONSTRUCTION MAY REQUIRE CHANGES TO ISSUED PERMITS OR OTHER APPROVALS FOR THE PROJECT, SUCH AS THE SITE AND DEVELOPMENT PLAN. CHANGES ARE NOT PERMITTED UNTIL THE APPROPRIATE APPROVALS HAVE BEEN OBTAINED.
- MAINTENANCE OF APPROVED PLANS/CONSTRUCTION PERPETUITY: THE PROPERTY OWNER IS REQUIRED TO MAINTAIN THE PROPERTY CONSISTENT WITH THE APPROVED PLANS IN PERPETUITY (UNLESS OTHERWISE PROVIDED IN THE APPROVED PLANS) ANY CHANGE TO LOCATION LAYOUT CONSTRUCTION, USE OR ANY OTHER MODIFICATION NOT CONSISTENT WITH THE APPROVED PLANS MAY REQUIRE MODIFICATION PERMITS AND MODIFICATIONS TO THE SITE PLAN APPROVAL AS APPLICABLE.
- DURATION OF SITE PLAN APPROVAL: A SITE PLAN APPROVAL IS VALID FOR TWO YEARS FROM THE DATE OF APPROVAL (A MAXIMUM ONE-YEAR EXTENSION MUST BE AUTHORIZED BY THE PLANNING COMMISSION), ALL PORTIONS OF A PROJECT NOT INITIATED THROUGH THE ISSUANCE OF BUILDING PERMITS SPECIFIC TO THAT PART OF THE PROJECT MUST BE ISSUED PRIOR TO THE EXPIRATION DATE OF THE SITE PLAN APPROVAL

	Sheet List Table
Sheet Number	Sheet Title
C1.1	COVER SHEET
C1.2	GENERAL NOTES
C1.3	AERIAL SITE PLAN
C1.4	EXISTING CONDITIONS PLAN
C1.5	INDEX PLAN
C1.6	SITE PLAN
C1.7	SITE PLAN
C1.8	SITE PLAN
C1.9	SUBPHASING PLAN
C2.1	BEST MANAGEMENT PRACTICES PLAN
C2.2	BEST MANAGEMENT PRACTICES DETAILS
C2.3	MASTER DRAINAGE PLAN
C2.4	PAVING GRADING AND DRAINAGE PLAN
C2.5	PAVING GRADING AND DRAINAGE PLAN
C2.6	PAVING GRADING AND DRAINAGE PLAN
C2.7	CITY OF VENICE PAVING AND SIDEWALK DETAILS
C2.8	STORMWATER DETAILS
C2.9	MISCELLANEOUS DETAILS
C3.101	MASTER UTILITY PLAN
C3.102	MASTER UTILITY PLAN
C3.103	MASTER UTILITY PLAN
C3.2	UTILITY PLAN AND PROFILE INDEX
C3.3	UTILITY PLAN AND PROFILE
C3.4	UTILITY PLAN AND PROFILE
C3.5	UTILITY PLAN AND PROFILE
C3.6	UTILITY PLAN AND PROFILE
C3.7	UTILITY PLAN AND PROFILE
C3.8	CITY OF VENICE WATER AND SEWER DETAILS
C3.9	CITY OF VENICE WATER AND SEWER DETAILS
C3.10	CITY OF VENICE WATER AND SEWER DETAILS

LAND USE DEVELOPMENT DATA

PRESENT ZONING:	15.85 ACRES PUD - PLANNED UNIT DEVELOPM	IENT	
ABUTTING ZONING:	WEST: INTERSTATE 75		
	EAST: PUD NORTH: PUD SOUTH: INTERSTATE 75		
PROJECT ADDRESS:	2600 RUSTIC RD AND NOKOMIS, FL 34275	1700 RANCH RD NOKOMIS, FL 34275	
PID:	0362-00-1002 & 0362-00-1007		
PROJECT AREA:	15.85 ACRES		
		S PER ACRE (MAXIMUM ALLOWED = 304 U	A 6,745 SQUARE FOOT AMENITY CENTER BUILDI JNITS TOTAL)
LAND USE: BUILDING (MULT	TI-FAMILY APARTMENTS + AMENIT	Y CENTER) 2.73 ACRES (17.22%)	
	ALKS, PAVERS AND PARKING ROL WATER EL.	5.40 ACRES (34.07%) 1.91 ACRES (12.05%) 5.81 ACRES (36.66%) 15.85 ACRES (100%)	
PROPOSED BUILDING	SETBACKS: BUILDING SETBACK F	ROM I-75 EQUAL TO BUILDING HEIGHT (1	:1).
	PROVIDED BY CITY OF VENICE.		
WATER: POTABLE WA	TER SUPPLY WILL BE FROM CITY	OF VENICE UTILITIES, BUT WILL BE MAST	TER METERED.
SEWER: WASTEWATE	R SERVICES WILL BE PROVIDED B	Y CITY OF VENICE UTILITIES.	
	PICKUP WILL BE PROVIDED BY CIT		
		ROM RANCH ROAD, RUSTIC ROAD, AND	CANOE BEND AVE.
	PRIVATELY MAINTAINED.		
LOADING ZONES REQ			
LOADING ZONES PRO			
	UIRED. REFER TO SEPARATE LAN		PERMIT. REFER TO PLTR21-00285. 1050 INCHES
COMMUNITY NO. 1211			ATE MAP FOR SARASOTA COUNTY, FLORIDA, GENCY MANAGEMENT AGENCY. FEMA DATUM I
ENVIRONMENTAL AND	D SURFACE WATER MANAGEMENT /ILL BE PRIVATELY MAINTAINED.	SYSTEM:	
<u>WELLS</u> : THERE ARE N	NO KNOWN EXISTING WELLS WITH	IN THE PROJECT BOUNDARY.	
IMPERVIOUS/PERVIOU IMPERVIOUS AREA: PERVIOUS AREA (INCL TOTAL:	<u>US AREAS:</u> <u>ACRES</u> <u>PERCENTAG</u> 8.13 51.3% L. LAKE): <u>7.72</u> <u>48.7%</u> 15.85 100%	<u>E</u>	
	STREET CROSSINGS AT CURBS, GU	JTTERS AND INTERSECTIONS SHALL CO	MPLY WITH THE AMERICANS WITH DISABILITIES
	A TREE PERMIT WAS ISSUED FOR T UIRED. REFER TO SEPARATE LAN		NG PERMIT. REFER TO PLTR21-00285. 1050 INCI
INCHES NEW TREES A	ARE REQUIRED. REFER TO SEPARA		RADING PERMIT. REFER TO PLTR21-00285. 105
REQUIRED PARKING (RESIDENTIAL USE: 2 S PRIVATE CLUBS: 1 SP	SPACES PER UNIT	CE PER 200 SQUARE FEET OF NON-STOP	RAGE AREA
	SPACES = 303 UNITS * 2 SPACES + JIRED = <u>640 SPACES REQUIRED (13</u>	6,745 SF AMENITY CENTER * (1 SPACE P 3 ADA)	ER 200 SF) = 606 SPACES + 34 SPACES
	SPACES = 19 (ADJACENT TO AMEN 'IDED = <u>485 SPACES PROVIDED (24</u>		MES) + 12 (2 GARAGES) + 430 (SURFACE)
		UTILITY COMP	ANIES:
		FPL	TECO GAS
		5657 NORTH McINTOSH ROAD SARASOTA, FLORIDA 34233	8261 VICO COURT SARASOTA, FLORIDA 34240-7844
		FRONTIER 1701 RINGLING BLVD. SARASOTA, FLORIDA 34236 941-906-6711	COMCAST CABLE 5205 FRUITVILLE ROAD SARASOTA, FLORIDA 34232
		VENICE UTILITIES 401 W. VENICE AVE. VENICE, FL 34285 (941)882-7297 CONTACT: PATIENCE ANATAS	10

dLS dLS ____



NDREW J. PLUTA, P.E. ON THE DATE ADJ PRINTED COPIES OF THIS DOCUMENT ARE NOT CON SIGNED AND SEALED AND THE SIGNATURE MUST BE ANDREW J. PLUTA, P.E. No.: 922

ANDREW J. PLUTA, P.E. FLA. P.E. LICENSE # 92225 CA. NO. 00035106

DATE:

07/15/2022

GENERAL CONSTRUCTION NOTES

- 1. THE CONTRACTOR AND SUBCONTRACTORS SHALL OBTAIN A COPY OF THE FLORIDA DEPARTMENT OF TRANSPORTATION "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION" (LATEST EDITION) AND BECOME FAMILIAR WITH THE CONTENTS PRIOR TO COMMENCING WORK, AND, UNLESS OTHERWISE NOTED, ALL WORK SHALL CONFORM AS APPLICABLE TO THESE STANDARDS AND SPECIFICATIONS.
- 2. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FURNISHING ALL MATERIAL AND LABOR TO CONSTRUCT THE FACILITY AS SHOWN AND DESCRIBED IN THE CONSTRUCTION DOCUMENTS IN ACCORDANCE WITH THE APPROPRIATE APPROVING AUTHORITIES, SPECIFICATIONS AND REQUIREMENTS. CONTRACTOR SHALL CLEAR AND GRUB ALL AREAS UNLESS OTHERWISE INDICATED, REMOVING TREES, STUMPS, ROOTS, MUCK, EXISTING PAVEMENT AND ALL OTHER DELETERIOUS MATERIAL.
- 3. EXISTING UTILITIES SHOWN ARE LOCATED ACCORDING TO THE INFORMATION AVAILABLE TO THE ENGINEER AT THE TIME OF THE TOPOGRAPHIC SURVEY AND HAVE NOT BEEN INDEPENDENTLY VERIFIED BY THE OWNER OR THE ENGINEER. GUARANTEE IS NOT MADE THAT ALL EXISTING UNDERGROUND UTILITIES ARE SHOWN OR THAT THE LOCATION OF THOSE SHOWN ARE ENTIRELY ACCURATE. FINDING THE ACTUAL LOCATION OF ANY EXISTING UTILITIES IS THE CONTRACTOR'S RESPONSIBILITY AND SHALL BE DONE BEFORE HE COMMENCES ANY WORK IN THE VICINITY. FURTHERMORE, THE CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR ANY AND ALL DAMAGES DUE TO THE CONTRACTOR'S FAILURE TO EXACTLY LOCATE AND PRESERVE ANY AND ALL UNDERGROUND UTILITIES. THE OWNER OR ENGINEER WILL ASSUME NO LIABILITY FOR ANY DAMAGES SUSTAINED OR COST INCURRED BECAUSE OF THE OPERATIONS IN THE VICINITY OF EXISTING UTILITIES OR STRUCTURES, NOR FOR TEMPORARY BRACING AND SHORING OF SAME. IF IT IS NECESSARY TO SHORE, BRACE, SWING OR RELOCATE A UTILITY, THE UTILITY COMPANY OR DEPARTMENT AFFECTED SHALL BE CONTACTED AND THEIR PERMISSION OBTAINED REGARDING THE METHOD TO USE FOR SUCH WORK.
- 4. IT IS THE CONTRACTOR'S RESPONSIBILITY TO CONTACT THE VARIOUS UTILITY COMPANIES WHICH MAY HAVE BURIED OR AERIAL UTILITIES WITHIN OR NEAR THE CONSTRUCTION AREA BEFORE COMMENCING WORK. THE CONTRACTOR SHALL PROVIDE 48 HOURS MINIMUM NOTICE TO ALL UTILITY COMPANIES PRIOR TO BEGINNING CONSTRUCTION. A LIST OF THE UTILITY COMPANIES WHICH THE CONTRACTOR <u>MUST</u> CALL BEFORE COMMENCING WORK IS PROVIDED ON THE COVER SHEET OF THESE CONSTRUCTION PLANS. THIS LIST SERVES AS A GUIDE ONLY AND IS NOT INTENDED TO LIMIT THE UTILITY COMPANIES WHICH THE CONTRACTOR MAY WISH TO NOTIFY.
- 5. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL REQUIRED CONSTRUCTION PERMITS AND BONDS IF REQUIRED PRIOR TO CONSTRUCTION.
- 6. THE CONTRACTOR SHALL HAVE AVAILABLE AT THE JOB SITE AT ALL TIMES ONE COPY OF THE CONSTRUCTION DOCUMENTS INCLUDING PLANS, SPECIFICATIONS, AND SPECIAL CONDITIONS AND COPIES OF ANY REQUIRED CONSTRUCTION PERMITS.
- 7. ANY DISCREPANCIES ON THE DRAWINGS SHALL BE IMMEDIATELY BROUGHT TO THE ATTENTION OF THE OWNER AND ENGINEER BEFORE COMMENCING WORK. NO FIELD CHANGES OR DEVIATIONS FROM DESIGN ARE TO BE MADE WITHOUT PRIOR APPROVAL OF THE OWNER AND NOTIFICATION TO THE ENGINEER.
- 8. ALL COPIES OF COMPACTION, CONCRETE AND OTHER REQUIRED TEST RESULTS ARE TO BE SENT TO THE OWNER AND DESIGN ENGINEER OF RECORD DIRECTLY FROM THE TESTING AGENCY.
- 9. THE CONTRACTOR SHALL BE RESPONSIBLE FOR SUBMITTING TO THE ENGINEER A CERTIFIED RECORD SURVEY SIGNED AND SEALED BY A PROFESSIONAL LAND SURVEYOR REGISTERED IN THE STATE OF FLORIDA DEPICTING THE ACTUAL FIELD LOCATION OF ALL CONSTRUCTED IMPROVEMENTS THAT ARE REQUIRED BY THE JURISDICTIONAL AGENCIES FOR THE CERTIFICATION PROCESS. ALL SURVEY COSTS WILL BE THE CONTRACTORS RESPONSIBILITY.
- 10. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DOCUMENTING AND MAINTAINING AS-BUILT INFORMATION WHICH SHALL BE RECORDED AS CONSTRUCTION PROGRESSES OR AT THE COMPLETION OF APPROPRIATE CONSTRUCTION INTERVALS AND SHALL BE RESPONSIBLE FOR PROVIDING AS-BUILT DRAWINGS TO THE OWNER FOR THE PURPOSE OF CERTIFICATION TO JURISDICTIONAL AGENCIES AS REQUIRED. ALL AS-BUILT DATA SHALL BE COLLECTED BY A STATE OF FLORIDA PROFESSIONAL LAND SURVEYOR WHOSE SERVICES ARE ENGAGED BY THE CONTRACTOR.
- 11. ANY WELLS DISCOVERED ON SITE THAT WILL HAVE NO USE MUST BE PLUGGED BY A LICENSED WELL DRILLING CONTRACTOR IN A MANNER APPROVED BY ALL JURISDICTIONAL AGENCIES. CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ANY WELL ABANDONMENT PERMITS REQUIRED.
- 12. ANY WELL DISCOVERED DURING EARTH MOVING OR EXCAVATION SHALL BE REPORTED TO THE APPROPRIATE JURISDICTIONAL AGENCIES WITHIN 24 HOURS AFTER DISCOVERY IS MADE.
- 13. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING THAT THE PROPOSED IMPROVEMENTS SHOWN ON THE PLANS DO NOT CONFLICT WITH ANY KNOWN EXISTING OR OTHER PROPOSED IMPROVEMENTS. IF ANY CONFLICTS ARE DISCOVERED, THE CONTRACTOR SHALL NOTIFY THE OWNER PRIOR TO INSTALLATION OF ANY PORTION OF THE SITE WORK THAT WOULD BE AFFECTED. FAILURE TO NOTIFY OWNER OF AN IDENTIFIABLE CONFLICT PRIOR TO PROCEEDING WITH INSTALLATION RELIEVES OWNER OF ANY OBLIGATION TO PAY FOR A RELATED CHANGE ORDER.

DEMOLITION NOTES

- 1. ALL MATERIAL REMOVED FROM THIS SITE BY THE CONTRACTOR SHALL BE DISPOSED OF BY THE CONTRACTOR IN A LEGAL MANNER.
- 2. REFER TO THE TOPOGRAPHIC SURVEY FOR ADDITIONAL DETAILS OF EXISTING STRUCTURES, ETC., LOCATED WITHIN THE PROJECT SITE. UNLESS OTHERWISE NOTED, ALL EXISTING BUILDINGS, STRUCTURES, SLABS, CONCRETE, ASPHALT, DEBRIS PILES, SIGNS, AND ALL APPURTENANCES ARE TO BE REMOVED FROM THE SITE BY THE CONTRACTOR AND PROPERLY DISPOSED OF IN A LEGAL MANNER AS PART OF THIS CONTRACT. SOME ITEMS TO BE REMOVED MAY NOT BE DEPICTED ON THE TOPOGRAPHIC SURVEY. IT IS THE CONTRACTOR'S RESPONSIBILITY TO VISIT THE SITE AND DETERMINE THE FULL EXTENT OF ITEMS TO BE REMOVED. IF ANY ITEMS ARE IN QUESTION, THE CONTRACTOR SHALL CONTACT THE OWNER PRIOR TO REMOVAL OF SAID ITEMS.
- 3. THE CONTRACTOR SHALL REFER TO THE DEMOLITION PLAN FOR DEMOLITION/PRESERVATION OF EXISTING TREES. ALL TREES NOT SPECIFICALLY SHOWN TO BE PRESERVED OR RELOCATED SHALL BE REMOVED AS A PART OF THIS CONTRACT. TREE PROTECTION FENCING SHALL BE INSTALLED PRIOR TO ANY DEMOLITION.

PAVING, GRADING AND DRAINAGE NOTES

- 1. ALL PAVING, CONSTRUCTION, MATERIALS, AND WORKMANSHIP WITHIN COUNTY'S RIGHT-OF-WAY SHALL BE IN ACCORDANCE WITH LOCAL OR COUNTY SPECIFICATIONS AND STANDARDS (LATEST EDITION) OR FDOT SPECIFICATIONS AND STANDARDS (LATEST EDITION) IF NOT COVERED BY LOCAL OR COUNTY REGULATIONS.
- 2. ALL UNPAVED AREAS IN EXISTING RIGHTS-OF-WAY DISTURBED BY CONSTRUCTION SHALL BE REGRADED AND SODDED.
- 3. TRAFFIC CONTROL ON ALL FDOT, LOCAL AND COUNTY RIGHTS-OF-WAY SHALL MEET THE REQUIREMENTS OF THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (U.S. DOT/FHA) AND THE REQUIREMENTS OF THE STATE AND ANY LOCAL AGENCY HAVING JURISDICTION. IN THE EVENT THAT THE CONTRACT DOCUMENTS AND THE JURISDICTIONAL AGENCY REQUIREMENTS ARE NOT IN AGREEMENT, THE MOST STRINGENT SHALL GOVERN.
- 4. THE CONTRACTOR SHALL GRADE THE SITE TO THE ELEVATIONS INDICATED AND SHALL REGRADE WASHOUTS WHERE THEY OCCUR AFTER EVERY RAINFALL UNTIL A GRASS STAND IS WELL ESTABLISHED OR ADEQUATE STABILIZATION OCCURS.
- 5. ALL OPEN AREAS WITHIN THE PROJECT SITE SHALL BE SODDED UNLESS INDICATED OTHERWISE ON THE LANDSCAPE PLAN.
- 6. ALL AREAS INDICATED AS PAVEMENT SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE TYPICAL PAVEMENT SECTIONS AS INDICATED ON THE DRAWINGS.
- 7. WHERE EXISTING PAVEMENT IS INDICATED TO BE REMOVED AND REPLACED, THE CONTRACTOR SHALL SAW CUT A MINIMUM 2" DEEP FOR A SMOOTH AND STRAIGHT JOINT AND REPLACE THE PAVEMENT WITH THE SAME TYPE AND DEPTH OF MATERIAL AS EXISTING OR AS INDICATED.
- 8. WHERE NEW PAVEMENT MEETS THE EXISTING PAVEMENT, THE CONTRACTOR SHALL SAW CUT THE EXISTING PAVEMENT A MINIMUM 2" DEEP FOR A SMOOTH AND STRAIGHT JOINT AND MATCH THE EXISTING PAVEMENT ELEVATION WITH THE PROPOSED PAVEMENT UNLESS OTHERWISE INDICATED.
- 9. THE CONTRACTOR SHALL INSTALL FILTER FABRIC OVER ALL DRAINAGE STRUCTURES FOR THE DURATION OF CONSTRUCTION AND UNTIL ACCEPTANCE OF THE PROJECT BY THE OWNER. ALL DRAINAGE STRUCTURES SHALL BE CLEANED OF DEBRIS AS REQUIRED DURING AND AT THE END OF CONSTRUCTION TO PROVIDE POSITIVE DRAINAGE FLOWS.
- 10. IF DEWATERING IS REQUIRED, THE CONTRACTOR SHALL OBTAIN ANY APPLICABLE REQUIRED PERMITS. THE CONTRACTOR IS TO COORDINATE WITH THE OWNER AND THE DESIGN ENGINEER PRIOR TO ANY EXCAVATION.
- 11. STRIP TOPSOIL AND ORGANIC MATTER FROM ALL AREAS OF THE SITE AS REQUIRED. IN SOME CASES TOPSOIL MAY BE STOCKPILED ON SITE FOR PLACEMENT WITHIN LANDSCAPED AREAS BUT ONLY AS DIRECTED BY THE OWNER.
- 12. FIELD DENSITY TESTS SHALL BE TAKEN AT INTERVALS IN ACCORDANCE WITH THE LOCAL JURISDICTIONAL AGENCY OR TO FDOT STANDARDS. IN THE EVENT THAT THE CONTRACT DOCUMENTS AND THE JURISDICTIONAL AGENCY REQUIREMENTS ARE NOT IN AGREEMENT, THE MOST STRINGENT SHALL GOVERN.
- 13. ALL SLOPES AND AREAS DISTURBED BY CONSTRUCTION SHALL BE GRADED AS PER PLANS. THE AREAS SHALL THEN BE SODDED OR SEEDED AS SPECIFIED IN THE PLANS, FERTILIZED, MULCHED, WATERED AND MAINTAINED UNTIL HARDY GRASS GROWTH IS ESTABLISHED IN ALL AREAS. ANY AREAS DISTURBED FOR ANY REASON PRIOR TO FINAL ACCEPTANCE OF THE JOB SHALL BE CORRECTED BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER. ALL EARTHEN AREAS WILL BE SODDED OR SEEDED AND MULCHED AS SHOWN ON THE LANDSCAPING PLAN.
- 14. ALL CUT OR FILL SLOPES SHALL BE 4 (HORIZONTAL) :1 (VERTICAL) OR FLATTER UNLESS OTHERWISE SHOWN.
- 15. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE CONTROL OF DUST AND DIRT RISING AND SCATTERING IN THE AIR DURING CONSTRUCTION AND SHALL PROVIDE WATER SPRINKLING OR OTHER SUITABLE METHODS OF CONTROL. THE CONTRACTOR SHALL COMPLY WITH ALL GOVERNING REGULATIONS PERTAINING TO ENVIRONMENTAL PROTECTION.
- 16. THE CONTRACTOR SHALL TAKE ALL REQUIRED MEASURES TO CONTROL TURBIDITY, INCLUDING BUT NOT LIMITED TO THE INSTALLATION OF TURBIDITY BARRIERS AT ALL LOCATIONS WHERE THE POSSIBILITY OF TRANSFERRING SUSPENDED SOLIDS INTO THE RECEIVING WATER BODY EXISTS DUE TO THE PROPOSED WORK. TURBIDITY BARRIERS MUST BE MAINTAINED IN EFFECTIVE CONDITION AT ALL LOCATIONS UNTIL CONSTRUCTION IS COMPLETED AND DISTURBED SOIL AREAS ARE STABILIZED. THEREAFTER, THE CONTRACTOR MUST REMOVE THE BARRIERS. AT NO TIME SHALL THERE BE ANY OFF-SITE DISCHARGE WHICH VIOLATES THE WATER QUALITY STANDARDS IN CHAPTER 17-302, FLORIDA ADMINISTRATIVE CODE.
- 17. SOD, WHERE CALLED FOR, MUST BE INSTALLED AND MAINTAINED ON EXPOSED SLOPES WITHIN 48 HOURS OF COMPLETING FINAL GRADING, AND AT ANY OTHER TIME AS NECESSARY, TO PREVENT EROSION, SEDIMENTATION OR TURBID DISCHARGES.
- 18. THE CONTRACTOR MUST REVIEW AND MAINTAIN A COPY OF THE ENVIRONMENTAL RESOURCE PERMIT COMPLETE WITH ALL CONDITIONS, ATTACHMENTS, EXHIBITS, AND PERMIT MODIFICATIONS IN GOOD CONDITION AT THE CONSTRUCTION SITE. THE COMPLETE PERMIT MUST BE AVAILABLE FOR REVIEW UPON REQUEST BY WATER MANAGEMENT DISTRICT REPRESENTATIVES.
- 19. THE CONTRACTOR SHALL ENSURE THAT ISLAND PLANTING AREAS AND OTHER PLANTING AREAS ARE NOT COMPACTED AND DO NOT CONTAIN ROAD BASE MATERIALS. THE CONTRACTOR SHALL ALSO EXCAVATE AND REMOVE ALL UNDESIRABLE MATERIAL FROM ALL AREAS ON THE SITE TO BE PLANTED AND PROPERLY DISPOSED OF IN A LEGAL MANNER.
- 20. THE CONTRACTOR SHALL INSTALL ALL UNDERGROUND STORM WATER PIPING PER MANUFACTURER'S RECOMMENDATIONS.

WATER AND SEWER UTILITY NOTES

- 1. THE CONTRACTOR SHALL CONSTRUCT GRAVITY SEWER LATERALS, MANHOLES GRAVITY SEWER LINES AND DOMESTIC WATER AND FIRE PROTECTION SYSTEM AS SHOWN ON THESE PLANS. THE CONTRACTOR SHALL FURNISH ALL NECESSARY MATERIALS, EQUIPMENT, MACHINERY, TOOLS, MEANS OF TRANSPORTATION AND LABOR NECESSARY TO COMPLETE THE WORK IN FULL AND COMPLETE ACCORDANCE WITH THE SHOWN, DESCRIBED AND REASONABLY INTENDED REQUIREMENTS OF THE CONTRACT DOCUMENTS AND JURISDICTIONAL AGENCY REQUIREMENTS. IN THE EVENT THAT THE CONTRACT DOCUMENTS AND THE JURISDICTIONAL AGENCY REQUIREMENTS ARE NOT IN AGREEMENT, THE MOST STRINGENT SHALL GOVERN.
- 2. ALL EXISTING UNDERGROUND UTILITY LOCATIONS SHOWN ARE APPROXIMATE. THE CONTRACTOR SHALL COMPLY WITH ALL REQUIREMENTS FOR UTILITY LOCATION AND COORDINATION IN ACCORDANCE WITH THE NOTES CONTAINED IN THE GENERAL CONSTRUCTION SECTION OF THIS SHEET.
- 3. THE CONTRACTOR SHALL RESTORE ALL DISTURBED VEGETATION IN KIND, UNLESS SHOWN OTHERWISE.
- 4. DEFLECTION OF PIPE JOINTS AND CURVATURE OF PIPE SHALL NOT EXCEED THE MANUFACTURER'S SPECIFICATIONS. SECURELY CLOSE ALL OPEN ENDS OF PIPE AND FITTINGS WITH A WATERTIGHT PLUG WHEN WORK IS NOT IN PROGRESS. THE INTERIOR OF ALL PIPES SHALL BE CLEAN AND JOINT SURFACES WIPED CLEAN AND DRY AFTER THE PIPE HAS BEEN LOWERED INTO THE TRENCH. VALVES SHALL BE PLUMB AND LOCATED ACCORDING TO THE PLANS.
- 5. ALL PHASES OF INSTALLATION, INCLUDING UNLOADING, TRENCHING, LAYING AND BACK FILLING, SHALL BE DONE IN A FIRST CLASS WORKMANLIKE MANNER. ALL PIPE AND FITTINGS SHALL BE CAREFULLY STORED FOLLOWING MANUFACTURER'S RECOMMENDATIONS. CARE SHALL BE TAKEN TO AVOID DAMAGE TO THE COATING OR LINING IN ANY D.I. PIPE FITTINGS. ANY PIPE OR FITTING WHICH IS DAMAGED OR WHICH HAS FLAWS OR IMPERFECTIONS WHICH, IN THE OPINION OF THE ENGINEER OR OWNER, RENDERS IT UNFIT FOR USE, SHALL NOT BE USED. ANY PIPE NOT SATISFACTORY FOR USE SHALL BE CLEARLY MARKED AND IMMEDIATELY REMOVED FROM THE JOB SITE, AND SHALL BE REPLACED AT THE CONTRACTOR'S EXPENSE.
- 6. WATER FOR FIRE FIGHTING SHALL BE AVAILABLE FOR USE PRIOR TO COMBUSTIBLES BEING BROUGHT ON SITE.
- 7. ALL UTILITY AND STORM DRAIN TRENCHES LOCATED UNDER AREAS TO RECEIVE PAVING SHALL BE COMPLETELY BACK FILLED IN ACCORDANCE WITH THE GOVERNING JURISDICTIONAL AGENCY'S SPECIFICATIONS. IN THE EVENT THAT THE CONTRACT DOCUMENTS AND THE JURISDICTIONAL AGENCY REQUIREMENTS ARE NOT IN AGREEMENT, THE MOST STRINGENT SHALL GOVERN.
- 8. UNDERGROUND LINES SHALL BE SURVEYED BY A STATE OF FLORIDA PROFESSIONAL LAND SURVEYOR PRIOR TO BACK FILLING.
- 9. CONTRACTOR SHALL PERFORM, AT HIS OWN EXPENSE, ANY AND ALL TESTS REQUIRED BY THE SPECIFICATIONS AND/OR ANY AGENCY HAVING JURISDICTION. THESE TESTS MAY INCLUDE, BUT MAY NOT BE LIMITED TO, INFILTRATION AND EXFILTRATION, TELEVISION INSPECTION AND A MANDREL TEST ON GRAVITY SEWER. A COPY OF THE TEST RESULTS SHALL BE PROVIDED TO THE UTILITY PROVIDER, OWNER AND JURISDICTIONAL AGENCY AS REQUIRED.

EROSION CONTROL NOTES

- 1. THE STORM WATER POLLUTION PREVENTION PLAN ("SWPPP") IS COMPRISED OF THIS EROSION CONTROL PLAN, THE STANDARD DETAILS, THE PLAN NARRATIVE, ATTACHMENTS INCLUDED IN SPECIFICATIONS OF THE SWPPP, PLUS THE PERMIT AND ALL SUBSEQUENT REPORTS AND RELATED DOCUMENTS.
- 2. ALL CONTRACTORS AND SUBCONTRACTORS INVOLVED WITH STORM WATER POLLUTION PREVENTION SHALL OBTAIN A COPY OF THE STORM WATER POLLUTION PREVENTION PLAN AND THE STATE OF FLORIDA NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM GENERAL PERMIT (NPDES PERMIT) AND BECOME FAMILIAR WITH THEIR CONTENTS.
- 3. THE CONTRACTOR SHALL IMPLEMENT BEST MANAGEMENT PRACTICES AS REQUIRED BY THE SWPPP. ADDITIONAL BEST MANAGEMENT PRACTICES SHALL BE IMPLEMENTED AS DICTATED BY CONDITIONS AT NO ADDITIONAL COST TO THE OWNER THROUGHOUT ALL PHASES OF CONSTRUCTION.
- 4. BEST MANAGEMENT PRACTICES (BMP'S) AND CONTROLS SHALL CONFORM TO FEDERAL, STATE, OR LOCAL REQUIREMENTS OR MANUAL OF PRACTICE, AS APPLICABLE. THE CONTRACTOR SHALL IMPLEMENT ADDITIONAL CONTROLS AS DIRECTED BY THE PERMITTING AGENCY OR OWNER.
- 5. EROSION CONTROL PLAN MUST CLEARLY DELINEATE ALL STATE WATERS. PERMITS FOR ANY CONSTRUCTION ACTIVITY IMPACTING STATE WATERS OR REGULATED WETLANDS MUST BE MAINTAINED ON SITE AT ALL TIMES.
- 6. THE CONTRACTOR SHALL MINIMIZE CLEARING TO THE MAXIMUM EXTENT PRACTICAL OR AS REQUIRED BY THE GENERAL PERMIT.
- CONTRACTOR SHALL DENOTE ON PLAN THE TEMPORARY PARKING AND STORAGE AREA WHICH SHALL ALSO BE USED AS THE EQUIPMENT MAINTENANCE AND CLEANING AREA, EMPLOYEE PARKING AREA, AND AREA FOR LOCATING PORTABLE FACILITIES, OFFICE TRAILERS, AND TOILET FACILITIES.
- 8. ALL WASH WATER (CONCRETE TRUCKS, VEHICLE CLEANING, EQUIPMENT CLEANING, ETC.) SHALL BE DETAINED AND PROPERLY TREATED OR DISPOSED.
- 9. SUFFICIENT OIL AND GREASE ABSORBING MATERIALS AND FLOTATION BOOMS SHALL BE MAINTAINED ON SITE OR READILY AVAILABLE TO CONTAIN AND CLEAN-UP FUEL OR CHEMICAL SPILLS AND LEAKS.
- 10. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DUST CONTROL ON SITE. THE USE OF MOTOR OILS AND OTHER PETROLEUM BASED OR TOXIC LIQUIDS FOR DUST SUPPRESSION OPERATIONS IS PROHIBITED.
- 11. RUBBISH, TRASH, GARBAGE, LITTER, OR OTHER SUCH MATERIALS SHALL BE DEPOSITED INTO SEALED CONTAINERS. MATERIALS SHALL BE PREVENTED FROM LEAVING THE PREMISES THROUGH THE ACTION OF WIND OR STORM WATER DISCHARGE INTO DRAINAGE DITCHES OR WATERS OF THE STATE.
- 12. ALL STORM WATER POLLUTION PREVENTION MEASURES PRESENTED ON THE PLAN, SHALL BE INITIATED AS SOON AS PRACTICABLE.


EROSION CONTROL NOTES (CONT.)

- 13. STABILIZATION PRACTICES SHOULD BE INITIATED AS SOON AS PRACTICAL, BUT IN NO CASE MORE THAN 7 DAYS WHERE CONSTRUCTION HAS TEMPORARILY CEASED.
- 14. DISTURBED PORTIONS OF THE SITE WHERE CONSTRUCTION ACTIVITY HAS PERMANENTLY STOPPED SHALL BE PERMANENTLY SEEDED. THESE AREAS SHALL BE SEEDED NO LATER THAN 7 DAYS AFTER THE LAST CONSTRUCTION ACTIVITY OCCURRED IN THESE AREAS. REFER TO SECTION 981 OF THE STANDARD SPECIFICATIONS FOR SEEDING AND MAINTENANCE REQUIREMENTS.
- 15. IF THE ACTION OF VEHICLES TRAVELING OVER THE GRAVEL CONSTRUCTION ENTRANCES IS NOT SUFFICIENT TO REMOVE THE MAJORITY OF DIRT OR MUD, THEN THE TIRES MUST BE WASHED BEFORE THE VEHICLES ENTER A PUBLIC ROAD. IF WASHING IS USED, PROVISIONS MUST BE MADE TO INTERCEPT THE WASH WATER AND TRAP THE SEDIMENT BEFORE IT IS CARRIED OFF THE SITE.
- 16. ALL MATERIALS SPILLED, DROPPED, WASHED, OR TRACKED FROM VEHICLES ONTO ROADWAYS OR INTO STORM DRAINS MUST BE REMOVED AS SOON AS POSSIBLE.
- 17. THE CONTRACTOR SHALL BE RESPONSIBLE FOR REMOVING SEDIMENT IN THE DETENTION POND AND ANY SEDIMENT THAT MAY HAVE COLLECTED IN THE STORM SEWER DRAINAGE SYSTEMS IN CONJUNCTION WITH THE STABILIZATION OF THE SITE.
- 18. ON-SITE & OFF SITE SOIL STOCKPILE AND BORROW AREAS SHALL BE PROTECTED FROM EROSION AND SEDIMENTATION THROUGH IMPLEMENTATION OF BEST MANAGEMENT PRACTICES. STOCKPILE AND BORROW AREA LOCATIONS SHALL BE NOTED ON THE EROSION CONTROL PLAN AND PERMITTED IN ACCORDANCE WITH GENERAL PERMIT REQUIREMENTS.
- 19. SLOPES SHALL BE LEFT IN A ROUGHENED CONDITION DURING THE GRADING PHASE TO REDUCE RUNOFF VELOCITIES AND EROSION.
- 20. DUE TO GRADE CHANGES DURING THE DEVELOPMENT OF THE PROJECT, THE CONTRACTOR SHALL BE RESPONSIBLE FOR ADJUSTING THE EROSION CONTROL MEASURES (SILT FENCES, ETC.) TO PREVENT EROSION.
- 21. ALL CONSTRUCTION SHALL BE STABILIZED AT THE END OF EACH WORKING DAY, THIS INCLUDES BACK FILLING OF TRENCHES FOR UTILITY CONSTRUCTION AND PLACEMENT OF GRAVEL OR BITUMINOUS PAVING FOR ROAD CONSTRUCTION.


MAINTENANCE

ALL MEASURES STATED ON THE EROSION AND SEDIMENT CONTROL PLAN, AND IN THE STORM WATER POLLUTION PREVENTION PLAN, SHALL BE MAINTAINED IN FULLY FUNCTIONAL CONDITION UNTIL NO LONGER REQUIRED FOR A COMPLETED PHASE OF WORK OR FINAL STABILIZATION OF THE SITE. ALL EROSION AND SEDIMENTATION CONTROL MEASURES SHALL BE CHECKED BY A QUALIFIED PERSON AT LEAST ONCE EVERY SEVEN CALENDAR DAYS AND WITHIN 24 HOURS OF THE END OF A 0.5" RAINFALL EVENT, AND CLEANED AND REPAIRED IN ACCORDANCE WITH THE FOLLOWING:

- 1. INLET PROTECTION DEVICES AND BARRIERS SHALL BE REPAIRED OR REPLACED IF THEY SHOW SIGNS OF UNDERMINING, OR DETERIORATION.
- 2. ALL SEEDED AREAS SHALL BE CHECKED REGULARLY TO SEE THAT A GOOD STAND IS MAINTAINED. AREAS SHOULD BE FERTILIZED, WATERED AND RESEEDED AS NEEDED. FOR MAINTENANCE REQUIREMENTS REFER TO SECTION 981 OF THE STANDARD SPECIFICATIONS.
- 3. SILT FENCES SHALL BE REPAIRED TO THEIR ORIGINAL CONDITIONS IF DAMAGED. SEDIMENT SHALL BE REMOVED FROM THE SILT FENCES WHEN IT REACHES ONE-HALF THE HEIGHT OF THE SILT FENCE.
- 4. THE CONSTRUCTION ENTRANCES SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOW OF MUD ONTO PUBLIC RIGHTS-OF-WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING OF THE CONSTRUCTION ENTRANCES AS CONDITIONS DEMAND.
- 5. THE TEMPORARY PARKING AND STORAGE AREA SHALL BE KEPT IN GOOD CONDITION (SUITABLE FOR PARKING AND STORAGE). THIS MAY REQUIRE PERIODIC TOP DRESSING OF THE TEMPORARY PARKING AS CONDITIONS DEMAND.
- 6. OUTLET STRUCTURES IN THE SEDIMENTATION BASINS SHALL BE MAINTAINED IN OPERATIONAL CONDITIONS AT ALL TIMES. SEDIMENT SHALL BE REMOVED FROM SEDIMENT BASINS OR TRAPS WHEN THE DESIGN CAPACITY HAS BEEN REDUCED BY 55 CUBIC YARDS / ACRE.
- 7. ALL MAINTENANCE OPERATIONS SHALL BE DONE IN A TIMELY MANNER BUT IN NO CASE LATER THAN 2 CALENDAR DAYS FOLLOWING THE INSPECTION.



					No. REVISIONS DATE BY
		© 2022 KIMLEY-HORN AND ASSOCIATES, INC.	1777 MAIN STREET, SUITE 200, SARASOTA, FL 34236	PHONE: 941-379-7600 WWW.KIMLEY-HORN.COM REGISTRY NO. 35106	
LICENSED PROFESSIONAL	ANDREW J. PLUTA. P.E.		FLORIDA LICENSE NUMBER	97779	DATE:
KHA PROJECT 248016000	DATE JUNE 2022	SCALE AS SHOWN	DESIGNED BY	DRAWN BY	СНЕСКЕД ВҮ
GENERAL NOTES					
RANCH ROAD	MUI TI-FAMII Y			SCP ACQUISITIONS, LLC	CITY OF VENICE FLORIDA
			ò	5	NTY O





4' Hog Wire Fer

DESCRIPTION:

The land referred to herein below is situated in the County of Sarasota, State of Florida,and described as follows:

A Parcel of land being and lying in Section 20, Township 38 South, Range 19 East, Sarasota County, Florida, and being more particularly described as follows:

Commence at the Southwest corner of the Northwest 1/4 of Section 20, Township 38 South, Range 19 East, Sarasota County, Florida; thence N 89°55'13" E, a distance of 2606.83 feet to the POINT OF BEGINNING; thence continue, N 89°55'13" E, a distance of 1054.23 feet; thence Southeasterly, 21.80 feet along the arc of a non-tangent curve to the left having a radius of 230.00 feet and a central angle of 05°25'52" (chord bearing of S 65°00'54" E, 21.79 feet); thence Southeasterly, 45.53 feet along the arc of a reverse curve to the right having a radius of 30.00 feet and a central angle of 86°57'07" (chord bearing of S 24°15'17" E, 41.28 feet) to the Westerly right-of-way of the Access Road under I-75; thence along said Westerly right-of-way, S 1913'17" W a distance of 1133.95 feet to the Northeasterly limited access right-of-way of I-75 (also known as State Road 93), thence along said Northeasterly limited access right-of-way, Northwesterly, 1255.91 feet along the arc of a non-tangent curve to the right having a radius of 17975.40 feet and a central angle of 04°00'11" (chord bearing N 37°06'52" W, 1255.66 feet); thence departing said limited access right-of-way, N 19°13'53" E, a distance of 121.60 feet; to the POINT OF BEGINNING

REPORT OF SURVEY:


- 1. This plat represents a Boundary Survey showing visible improvements.
- 2. Bearings shown hereon refer to an assumed meridian, West line of Section $5-39-19 = N.00^{\circ}14'30''E.$
- 3. There may exist other underground fixed interior improvements, which are not visible and are not a part of this survey.
- 4. Description shown hereon has been taken from Title Commitment Furnished. See Note #6.
- 5. Subject to easements and rights of way of record, if any. No research has been made of easements or rights has of ways of record. No easements shown on Record Plat.
- 6. This plat has been prepared with the benefit of a ALTA Commitment for Title Insurance issuded by First American Title Insurance Company, File No. 2021-5623729, dated October 05, 2021 at 8:00 AM.
- 7. Parcel shown hereon is situated in Flood Zone "X", base flood elevation Not determined, per current Flood Insurance Rate Map 12115C0245F, Index Map dated November 4, 2016.
- 8. Accuracy: The expected use of the land is "Suburban". The minimum relative distance accuracy for this type of boundary survey is 1 foot in 7,500 feet. The accuracy obtained by measurement and calculation of a closed geometric figure was found to exceed this requirement.
- 9. (D) Denotes information obtained from Deed. 10. (F) Denotes information obtained from Field measurement.
- 11. Review of Schedule "B–II" of First American Title
- Insurance Company ALTA Commitment for Title Insurance, see note # 6 above.
- Items 1, 2, 3, 4, 5, 6, 7, 8, and 22 are not a matter of Land Surveying, and not depicted hereon.
- Items 9, 10, 13, 17, 18, 19, and 20 are not applicable, and depicted hereon.
- Items 12, 15, and 16 are applicable and depicted hereon.
- ltems 11 and 14 are applicable as access easements which are offsite, and not depicted hereon.
- Item 21 is applicable and blanket in nature, and not depicted hereon.


NOTE:


(NAVD 88) based on National Geodetic Survey Benchmark "I75 83 A31 RM 1", having a published elevation of 38.41 feet (NAVD 88).

4' Hog Wire F

No. 4 (OSW)







GR 4	APHIC SCALE IN FEET							
	LEGEND:							
F	TYPE "F" CURB							
RF)	REVOLVED TYPE "F" CURB (24")							
$\tilde{\mathbf{D}}$	TYPE "D" CURB							
F) RF) D) M	TYPE "M" CURB							
R R	FLUSH CURB AND SIDEWALK							
R	CURB RAMP							
\preceq	5' TRANSITION BETWEEN TWO TYPES OF CURB							
#)	PARKING COUNT		2				200 2	
	PROPOSED ASPHALT PAVEMENT (REFER TO PAVEMENT SECTION ON SHEET C2.7)		IN C	5		TES, INC.	Ý.	
	CONCRETE PAVEMENT	1				SOCIATES	SARASUI 1-7600	いい
	PAVERS					© 2022 KIMLEY-HORN AND ASS		
NAGE	& PAVEMENT MARKING LEGEND							
		١٩L			Ļ	C	Ч	

PLUTA

Z 4

Ω

SITE

C

PREPARED FOR

Q

Ω

SC

ROAD

RANCH

AMIL

Ц


F


MU

SHEET NUMBER


C1.6


- <u>SIG</u>
- 4" WIDE SOLID WHITE STRIPE
- 2 4" WIDE SOLID BLUE STRIPE
- $\overline{3}$ 6" WIDE SOLID WHITE STRIPE (LANE LINE)
- $\langle \mathbf{4} \rangle$ 12" WIDE SOLID WHITE LINE (STANDARD CROSSWALK)
- 5 24" WIDE SOLID WHITE LINE (STOP LINE)
- 6 18" WIDE SOLID YELLOW LINE (GORE)
- $\langle 7 \rangle$ HANDICAP PARKING (SEE SHEET B-7 FOR DETAILS)
- A "STOP" SIGN & POST (R1-1, W/R, 30"x30")
- B 25 M.P.H. SPEED LIMIT SIGN & POST (R2-1, B/W, 24"x30")
- C PEDESTRIAN CROSSING SIGN AND POST (W11-2, B/Y, 30"x30")
- D HANDICAP PARKING SIGN AND POST (R7-8)
- E "KEEP RIGHT" (GRAPHIC) SIGN AND POST (R4-7, B/W, 24"x30") AND 18"x18" REFLECTOR TYPE I AMBER OBJECT MARKER (OM1-3)
- NOTES: 1. ALL EDGE OF PAVEMENT RADII ARE 3', UNLESS OTHERWISE NOTED. 2. ALL HANDICAP RAMPS (CR) SHALL BE CONSTRUCTED WITH TACTILE SURFACES. SEE DETAIL ENG-1 ON SHEET C2.7.








C1.7











<u>LEGEND</u>

- SILT FENCE

Ο INLET PROTECTION

2 TYP.

TYPICAL BEST MANAGEMENT DEVICE LOCATION. SEE BMP DETAIL DRAWING FOR BMP PLACEMENT

AND DETAILS. (SHEET B-2)


BEST MANAGEMENT PRACTICE GUIDELINES


- TYPICAL BEST MANAGEMENT DEVICE LOCATION. _#_ > SEE BMP DETAIL DRAWING FOR BMP PLACEMENT
- **TYP** / AND DETAILS. (SHEET B-2)
- 1. THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING ALL NECESSARY BMP DEVICES THROUGH THE DURATION OF ALL CONSTRUCTION ACTIVITIES OR AS DIRECTED BY THE ENGINEER.
- 2. PRIOR TO ANY EARTHMOVING OPERATIONS, THE CONTRACTOR SHALL INSTALL ALL REQUIRED BMP DEVICES PER CITY OF VENICE. ALL BMP DEVICES SHALL BE LOCATED AS SHOWN ON PLANS.
- 3. ALL GRASSING BY EITHER SEED OR SOD SHALL BE INSTALLED AS SOON AS PRACTICAL UPON THE COMPLETION OF FINAL GRADING OPERATIONS. THE CONTRACTOR SHALL BE RESPONSIBLE TO MAINTAIN ALL GRASSING IN A HEALTHY GROWING ENVIRONMENT UNTIL ACCEPTANCE BY THE ENGINEER.
- 4. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE CONTROL OF WIND AND DUST DURING ALL PHASES OF CONSTRUCTION BY USING WATER TRUCKS, WIND FENCING OR OTHER DEVICES AS APPROVED BY THE ENGINEER.
- 5. THE CONTRACTOR SHALL BE RESPONSIBLE TO SAFELY STORE EQUIPMENT, FUEL, OIL AND OTHER HAZARDOUS DEVICES IN A MANNER TO PREVENT GREASE, OIL, FUEL AND OTHER HAZARDOUS SUBSTANCES FROM CONTAMINATING THE STORMWATER MANAGEMENT AND COLLECTION SYSTEMS AND PRESERVATION AREAS. ADDITIONAL BMP MEASURES MAY BE NECESSARY TO ENSURE
- THAT TURBID WATER IS NOT DISCHARGED FROM THE CONSTRUCTION SITE. THE CONTRACTOR IS RESPONSIBLE FOR MAINTAINING COMPLIANCE WITH THE STORMWATER POLLUTION PREVENTION PLAN, THE N.P.D.E.S. PERMIT AND THE CONDITIONS OF THE SWFWMD ENVIRONMENTAL RESOURCE


BEST MANAGEMENT PRACTICES NOTES:


PFRMIT


- 1. SILT FENCE SHOWN ON THESE PLANS SHALL BE INSTALLED IN THE LOCATIONS INDICATED AND ALONG THE OSW LINE UNLESS OTHERWISE NOTED ON THE PLANS. IF THERE IS A OSW IMPACT, ALL SILT FENCE SHALL BE INSTALLED 2' WATER WARD OF TOE OF SLOPE AS SHOWN ON THESE PLANS. NO SILT FENCE SHALL BE INSTALLED IN PRESERVED WETLANDS OR UPLANDS EXCEPT AS PROTECTION AROUND TEMPORARY IMPACTS.
- 2. BEST MANAGEMENT PRACTICES SHOWN FOR OPEN THROAT AND GRATED SWALE INLETS SHALL BE INSTALLED AS APPROPRIATE FOR VARIOUS PROJECT PHASES.
- 3. ALL LAKES SHALL BE SODDED FROM CWL TO 2' BACK OF LAKE CONTROL LINE (TOP OF BANK).
- 4. ALL CURBING, EDGE OF PAVEMENT WHERE CURB IS NOT PRESENT SHALL HAVE A 2' WIDE STRIP OF SOD.
- 5. ALL DRAINAGE STRUCTURES SHALL BE SODDED ALONG THE EDGE OF THE STRUCTURE 2' MINIMUM SOD WIDTH.
- 6. ALL DRAINAGE SWALES SHALL BE SODDED TO 2' BACK OF TOP OF BANK.
- 7. CONTRACTOR TO INSPECT AND REPAIR ALL BMP'S ON A WEEKLY BASIS. A LOG OF SUCH INSPECTIONS SHALL BE MAINTAINED AT THE SITE AND WILL BE SUBMITTED TO THE DISTRICT ON A MONTHLY BASIS.
- 8. ANY BMP IN NEED OF REPAIR OR REINSTALLATION SHALL BE CORRECTED BY THE CONTRACTOR WITHIN 24 HOURS OF IDENTIFICATION OF THE NEED FOR SUCH CORRECTION.
- 9. RECOMMENDED LOCATIONS OF THE TEMPORARY GRAVEL CONSTRUCTION ENTRANCES HAVE BEEN SHOWN ON THE PLANS. ALTERNATE LOCATIONS CAN BE PROPOSED BY THE CONTRACTOR AND SHALL BE APPROVED BY THE ENGINEER OF RECORD. THE CONTRACTOR SHALL BE RESPONSIBLE FOR UTILIZING TEMPORARY GRAVEL CONSTRUCTION ENTRANCES PER THE DETAIL PROVIDED ON THE SHEET B-2 FOR ENTRANCES TO THE PROJECT.
- DEWATERING NOTES:
- 1. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR THE ARRANGEMENT, LOCATION AND DEPTHS OF THE DEWATERING SYSTEM NECESSARY TO ACCOMPLISH THE WORK DESCRIBED ON THESE PLANS.
- 2. THE CONTRACTOR, IF REQUIRED, IS RESPONSIBLE FOR SUBMITTING TO THE SOUTHWEST FLORIDA WATER MANAGEMENT DISTRICT FOR REVIEW A DEWATERING PLAN AND SUPPORTING CALCULATIONS. THIS PLAN SHALL DETAIL THE DEWATERING METHODS PROPOSED, THE DURATION OF DEWATERING, FLOW PATHS, AND POINTS OF DISCHARGE.
- 3. ALL WATER REMOVED FROM THE EXCAVATIONS SHALL BE DISPOSED OF IN SUCH A MANNER AS WILL NOT ENDANGER PUBLIC HEALTH, DAMAGE PUBLIC OR PRIVATE PROPERTY, OR AFFECT ADVERSELY ANY PORTION OF THE WORK UNDER CONSTRUCTION OR COMPLETED.
- 4. PUBLIC RIGHTS-OF-WAY AND PROPERTIES SHALL NOT BE UTILIZED FOR THE DISPOSAL OF WATER REMOVED FROM THE GROUND BY THE DEWATERING PROCESS.
- 5. THE METHODS AND PROVISIONS UTILIZED TO PREVENT SILTATION AND EROSION SHALL CONFORM TO CURRENT FLORIDA DEPARTMENT OF ENVIRONMENTAL PROTECTION PRACTICES AND REGULATIONS AND ANY OTHER LOCAL LEGAL PROVISIONS WHICH MAY APPLY. IN THE EVENT OF CONFLICTING REQUIREMENTS, THE STRICTER REQUIREMENTS SHALL APPLY.
- 6. SHOULD DEWATERING BE REQUIRED, CONTRACTOR IS TO FOLLOW, AT A MINIMUM, THE TYPICAL DEWATERING DISCHARGE PLAN AS DETAILED ON SHEET B-2 FOR ALL PUMPED WATER.
- 7. THE PUMPING RATE SHALL BE MONITORED AND ADJUSTED, IF NECESSARY IN ORDER TO PREVENT THE DISCHARGE OF TURBID WATER INTO THE PUBLIC RIGHTS-OF-WAY OR EXISTING WETLANDS.
- 8. NO DIRECT PUMPING DISCHARGE IS PERMITTED INTO ANY EXISTING WETLANDS.




































C2.9












	GRAPHIC SCALE IN FEET 0 15 30 60	DATE BY
		REVISIONS
ROAD		Kimley » Horn © 2022 KIMLEY-HORN AND ASSOCIATES, INC. 1777 MAIN STREET, SUITE 200, SARASOTA, FL 34236 PHONE: 941–379–7600 WWW.KIMLEY-HORN.COM REGISTRY NO. 35106 No.
		KHA PROJECT 248016000LICENSED PROFESSIONAL DATE248016000DATE DATEJUNE 2022ANDREW J. PLUTA, P.E.JUNE 2022ANDREW J. PLUTA, P.E.SCALE AS SHOWN DESIGNED BYFLORIDA LICENSE NUMBER 92225DRAWN BY92225CHECKED BYDATE:CHECKED BYDATE:
		MASTER UTILITY PLAN
PROJECT DATUM: NAVD88 THE PRESENCE OF GROUNDWATER SHOULD BE ANTICIPATED ON THIS PROJECT. CONTRACTOR'S BID SHALL INCLUDE CONSIDERATION FOR ADDRESSING THIS ISSUE. THE SITE CONSTRUCTION STAKEOUT SHALL BE PREFORMED UNDER THE DIRECTION OF A FLORIDA REGISTERED SURVEYOR. AUTOCAD FILES WILL BE FURNISHED TO AID IN THE SITE CONSTRUCTION STAKEOUT. ANY DISCREPANCIES FOUND BETWEEN AUTOCAD FILES AND SITE CONSTRUCTION PLANS SHALL BE BROUGHT TO THE ENGINEER'S		RANCH ROAD MULTI-FAMILY PREPARED FOR PREPARED FOR SCP ACQUISITIONS, LLC CITY OF VENICE
SHALL BE BROUGHT TO THE ENGINEER'S ATTENTION FOR CLARIFICATION PRIOR TO THAT STAKEOUT.		SHEET NUMBER C3.102



Wire rence	No. REVISIONS DATE BY
10' LANDSCAPE	Kimley-Horn AND ASOCIATES, INC. © 2022 KIMLEY-HORN AND ASSOCIATES, INC. 1777 MAIN STREET, SUITE 200, SARASOTA, FL 34236 PHONE: 941-379-7600 WWW.KIMLEY-HORN.COM REGISTRY NO. 35106
	KHA PROJECT 248016000LICENSED PROFESSIONAL248016000DATEDATE JUNE 2022ANDREW J. PLUTA, P.E.JUNE 2022ANDREW J. PLUTA, P.E.SCALE AS SHOWNFLORIDA LICENSE NUMBERDESIGNED BYDESIGNED BYDRAWN BYCHECKED BYDRAWN BYDATEDATEDATEDATEDATE
	MASTER UTILITY PLAN
Teres or	RANCH ROAD RANCH ROAD NULTI-FAMILY NULTI-FAMILY REPARED FOR PREPARED FOR SCP ACOUISITIONS, LLC C3.103