MID FLORIDA DIESEL



2215 HIGHWAY 60 EAST BARTOW, FL. 33830 (863) 519-0107 FAX (863) 519-0109 WWW.MIDFLORIDADIESEL.COM

November 7, 2019

PROPOSAL

For

100 AMP Automatic Transfer Switch Florida Sheriff Association Bid FSA 19-VEH17.0 Specification #223

City of Venice

ATTN: Tim Merritt

(Quote # 11072019-JA)

Mid Florida Diesel submits the following proposal for the project: Lift Stations #29, 61,63,68 & 77

ASCO 300 Series AUTOMATIC TRANSFER SWITCH:

ASCO 300 G Series Poles: 3 100 amp Rated (Qty: 5) 240Volts, Three-Phase **Open-transition** Solid Neutral Withstand rating: 200,000 (With Current Limiting Fuses), 42,000 (Specific Breaker), N/A (Any Breaker) Test Switch Manual Bypass of Transfer to Normal TD **ATS Switch Position Indicating Lights** Source Available Indicating Lights Automatic Engine Exerciser with Load/No Load Selector Switch ATS Position Indicating Contacts (1 Normal, 1 Emergency) Provisions for Remote Transfer Contact (Peak Shaved) bypassed if Emergency Fails In-Phase Monitor for Motor Load Control Selective Load Disconnect Provisions for Inhibiting Transfer to Emergency Time Delay Momentary Outage Override (Normal) Time Delay Momentary Outage Override (Emergency) Time Delay Transfer to Emergency Time Delay Re-transfer to Normal Time Delay Engine Cool Down WARRANTY - Two (2) Year Basic ATS Standby Limited Warranty NEMA: 3R Steel Enclosure (Outdoor Mounting) Accessories: **Deluxe Exerciser**

MISCELLANEOUS:

Certified Factory Test Manual – One (1) Instruction Manuals 2 Yr. Standby Limited Warranty Test Acceptance Start-up by Factory Trained Representative (Start Up)

NOTES:

1. This proposal is our interpretation of your requirement and includes only the items listed. Should there be other requirements or specifications, we will re-quote accordingly.

2. Units are shipped wet to include lube oil and a 50/50 water and anti-freeze mix unless otherwise noted in this quotation.

3. Startup performed upon notification of completed installation by installing contractor.

4. CANCELLATION: Shall be subject to applicable fees but no less than 20% of the purchase price

6. EXCLUSIONS: Installation of any kind, Offloading of Generator, Placement of Generator on Pad, Fuel, Springs Isolator, Tank, Piping, and Insulation. We have not seen specs.

7. Start Up included in price

8. Freight included in the price. Off-loading of generator by others

9. Terms: Net 30 Day-- No retain age without written pre-accepted agreement.

Proposal Summary:

FSA Spec #223- 600 amp Transfer Switch Bid:	\$4,100.00
Deduct: Downgrade to 100amp Transfer Switch (Order Code: 104amp):	(\$2,210.00)
Sub-Total Price:	\$1,890.00*
*ADDER: NEMA 4X Stainless Steel Enclosure Specification #223	
(Order Code: 4X-100-260):	\$2,000.00
Total Price:	\$3,890.00 <u>X 5 ea.</u>
Grand Total Price:	\$19,450.00 (Tax Not Included)

Note

Quoted prices do not include Federal, State or Local taxes which may be applicable. Quoted prices include normal testing, packaging and instructional literature. Special testing, packaging, additional instructional literature, parts, provisioning lists or prints are not included, and prices will be quoted separately.

Quotation Firm for 30 Day(s) Delivery Notes: 7-9 Weeks

BY: _____ goe Antonini_

Joe Antonini Mid Florida Diesel, Inc.

MID FLORIDA DIESEL



2215 HIGHWAY 60 EAST BARTOW, FL. 33830 (863) 519-0107 FAX (863) 519-0109 WWW.MIDFLORIDADIESEL.COM

November 7th, 2019

PROPOSAL

For

30KW Diesel Generator Florida Sheriff Association Bid FSA 19-VEH17.0 Specification #99

City of Venice

ATTN: Tim Merritt

Mid Florida Diesel submits the following proposal for the project: Lift Stations #29,61,68 & 77

Blue Star Power Systems MODEL: (Qty. - 4) JD30-03IT4

(Quote # 11072019-JA)

GENERATOR: 30 kW, 38 kVA VOLTAGE: 240 volt Three-Phas

VOLTAGE: 240 volt Three-Phase ENGINE: John Deere 3029TFG89, 60 Hz Diesel, 1800 RPM

Standard Features Included:

Microprocessor based, digital readout control system.

Engine vitals monitored by LCD display: Oil pressure, Running time, Engine temperature, Safety shutdowns (HWT, OC, OS, OP, LWL), Battery voltage, Generator AC voltage, AC amperage, Frequency. Additional Features: Oil drain extension, Vibration isolation pads, Water heater, Fuel solenoid valve.

Selected Model Features Included: Isochronous Governor + / - .25%

UL2200 EPA Tier II Certified 130 Degree Temperature Rise

CONTROL PANEL:

DGC-2020 Control Panel (Expanded)

Blue Star DGC-2020 Microprocessor Based Gen-Set Controller Mounted Facing Left from Generator End (Unless Specified Otherwise) Standard Features: Low Oil Pressure, High Coolant Temp, Overspeed, Overcrank Shutdowns Emergency Stop Pushbutton, Audible Alarm Buzzer with Silencing Switch Optional Features Include: Generator Protection (Undervoltage, Overvoltage, Underfrequency, Overfrequency, Overcurrent) Included Accessories

ENCLOSURE: Weather Proof Steel Enclosure-- Level II Weather Proof Enclosure- Made with 14 Gauge Steel with louvered rear opening for air intake and punched side air openings for air intake and silencer is mounted inside enclosure with exhaust exiting through front sound compartment. Pitched roof for increased structural integrity and improved watershed. Lockable handles keyed alike with hinged doors **Accessories:** Sound Attenuation Foam 1.5"

200 mph Wind Load Rated Color-White

COOLING SYSTEM:

Unit Mounted Radiator Accessories: Low Coolant Level Shutdown

CIRCUIT BREAKERS:

100A BREAKER – 600v Thermal Magnetic 80% rated Mounted and Wired in a NEMA 1 Enclosure (Qty: (1 per gen) Circuit Breaker - UL listed and CSA certified. Accessories:

BATTERY:

Lead Acid Battery

BLOCK HEATER: 1000 Watt

Standard @ 20 F w/isolation valves 120v 1 phase

VIBRATION ISOLATION:

Vibration Pads Isolator

BATTERY CHARGER:

(12 Volt, 6 Amp) Included Accessories:

SUB BASE TANK:

Sub Base Fuel Tank Steel (with Stub Up) (70 Gallons Capacity-24hrs run time) Accessories: UL 142 Approved

Double Wall Emergency Pressure Relief Vent Cap Set (1/2 PSI) - 2" (1) 1.5" Normal Vent Cap

MUFFLER:

Critical Grade Muffler – Accessories: Rain Cap

MISCELLANEOUS:

Certified Factory Test Manual – One (1) Instruction Manuals 2 Yr/2000 Hr Standby Limited Warranty Test Acceptance Run by Factory Trained Representative (Start Up)

NOTES:

1. This proposal is our interpretation of your requirement and includes only the items listed. Should there be other requirements or specifications, we will requote accordingly.

2. Units are shipped wet to include lube oil and a 50/50 water and anti-freeze mix unless otherwise noted in this quotation.

3. Startup performed upon notification of completed installation by installing contractor.

4. CANCELLATION: Shall be subject to applicable fees but no less than 20% of the purchase price

6. EXCLUSIONS: Installation of any kind, Offloading of Generator, Placement of Generator on Pad, Fuel, Springs Isolator, Tank, Piping, and Insulation. We have not seen specs.

- 7. Start Up included in price
- 8. Freight included in the price. Off-loading of generator by others
- 9. Terms: Net 30 Day-- No retain age without written pre-accepted agreement.

Proposal Summary: FSA Spec #099 Delete Opt	FSA Spec #099 Standard Blue S tion-Downgrade to an 30KW (Orde		\$32,350.00 (<u>\$10,122.00)</u> \$22,228.00*
*ADDER: Level III AluminumEnclos *ADDER: Permanent Magnet Speci	ure Specification #099(Order Code- fication #099 (Order Code-PMG):	LV-AL-III-20-125): SubTotal:	\$3,610.00 <u>\$1,000.00</u> \$4,610.00*
ADDER: Coat the 70 gallon fuel ta (Order Code 30% discou	ank with extreme Liner: Specification int off List Price):	#099 List Price: Subtract 30%: Sub-Total Price:	\$1,042.00 <u>-(\$313.00)</u> \$729.00

Total Price: \$27,567.00*

Grand Total Price: \$110,268.00

(Tax Not Included)

Note: * See attached FSA Bid and Spec sheets

Quoted prices do not include Federal, State or Local taxes which may be applicable. Quoted prices include normal testing, packaging and instructional literature. Special testing, packaging, additional instructional literature, parts, provisioning lists or prints are not included, and prices will be quoted separately.

Quotation Firm for 30 Day(s) Delivery Notes: 12-14 Weeks

BY: _____ Joe Antonini__

Joe Antonini Mid Florida Diesel, Inc.

MID FLORIDA DIESEL



2215 HIGHWAY 60 EAST BARTOW, FL. 33830 (863) 519-0107 FAX (863) 519-0109 WWW.MIDFLORIDADIESEL.COM

November 7th, 2019

PROPOSAL

For

50KW Diesel Generator Florida Sheriff Association Bid FSA 19-VEH17.0 Specification #99

City of Venice

ATTN: Tim Merritt

Mid Florida Diesel submits the following proposal for the project: Lift Station #63

Blue Star Power Systems MODEL: (Qty. - 1) JD50-03

(Quote # 11072019-JA)

GENERATOR: 50 kW, 62.5 kVA VOLTAGE: 240 volt Three-Phase ENGINE: John Deere 4045HF280, 60 Hz Diesel, 1800 RPM

Standard Features Included:

Microprocessor based, digital readout control system.

Engine vitals monitored by LCD display: Oil pressure, Running time, Engine temperature, Safety shutdowns (HWT, OC, OS, OP, LWL), Battery voltage, Generator AC voltage, AC amperage, Frequency. Additional Features: Oil drain extension, Vibration isolation pads, Water heater, Fuel solenoid valve.

Selected Model Features Included: Isochronous Governor + / - .25%

UL2200 EPA Tier II Certified 130 Degree Temperature Rise

CONTROL PANEL:

DGC-2020 Control Panel (Expanded)

Blue Star DGC-2020 Microprocessor Based Gen-Set Controller Mounted Facing Left from Generator End (Unless Specified Otherwise) Standard Features: Low Oil Pressure, High Coolant Temp, Overspeed, Overcrank Shutdowns Emergency Stop Pushbutton, Audible Alarm Buzzer with Silencing Switch Optional Features Include: Generator Protection (Undervoltage, Overvoltage, Underfrequency, Overfrequency, Overcurrent) Included Accessories

ENCLOSURE: Weather Proof Steel Enclosure-- Level II Weather Proof Enclosure- Made with 14 Gauge Steel with louvered rear opening for air intake and punched side air openings for air intake and silencer is mounted inside enclosure with exhaust exiting through front sound compartment. Pitched roof for increased structural integrity and improved watershed. Lockable handles keyed alike with hinged doors **Accessories:** Sound Attenuation Foam 1.5"

200 mph Wind Load Rated Color-White

COOLING SYSTEM:

Unit Mounted Radiator Accessories: Low Coolant Level Shutdown

CIRCUIT BREAKERS:

100A BREAKER – 600v Thermal Magnetic 80% rated Mounted and Wired in a NEMA 1 Enclosure (Qty: (1 per gen) Circuit Breaker - UL listed and CSA certified. Accessories:

BATTERY:

Lead Acid Battery

BLOCK HEATER:

Standard @ 20 F w/isolation valves 120v 1 phase

VIBRATION ISOLATION:

Vibration Pads Isolator

BATTERY CHARGER:

(12 Volt, 6 Amp) Included Accessories:

SUB BASE TANK:

Sub Base Fuel Tank Steel (with Stub Up) (120 Gallons Capacity-24hrs run time) Accessories: UL 142 Approved

Double Wall Emergency Pressure Relief Vent Cap Set (1/2 PSI) - 2" (1) 1.5" Normal Vent Cap

MUFFLER:

Critical Grade Muffler – Accessories: Rain Cap

MISCELLANEOUS:

Certified Factory Test Manual – One (1) Instruction Manuals 2 Yr/3000 Hr Standby Limited Warranty Test Acceptance Run by Factory Trained Representative (Start Up)

NOTES:

1. This proposal is our interpretation of your requirement and includes only the items listed. Should there be other requirements or specifications, we will requote accordingly.

2. Units are shipped wet to include lube oil and a 50/50 water and anti-freeze mix unless otherwise noted in this quotation.

3. Startup performed upon notification of completed installation by installing contractor.

4. CANCELLATION: Shall be subject to applicable fees but no less than 20% of the purchase price

6. EXCLUSIONS: Installation of any kind, Offloading of Generator, Placement of Generator on Pad, Fuel, Springs Isolator, Tank, Piping, and Insulation. We have not seen specs.

- 7. Start Up included in price
- 8. Freight included in the price. Off-loading of generator by others
- 9. Terms: Net 30 Day-- No retain age without written pre-accepted agreement.

	FSA Spec #099 Standard Blue S n-Downgrade to an 50KW (Orde	er Code:JD50-03):	\$32,350.00 - <u>(\$7,474.00)</u> \$24,876.00*
*ADDER: Level III Aluminum Enclosure *ADDER: Permanent Magnet Specifica	· ·	LV-AL-III-20-125): SubTotal:	\$3,610.00 <u>\$1,000.00</u> \$4,610.00*
ADDER: Coat the 120 gallon fuel tan (Order Code 30% discount)	•	List Price: Subtract 30%: Sub-Total Price:	\$1,667.00 <u>-(\$501.00)</u> \$1,166.00

Total Price: \$30,652.00

(Tax Not Included)

Note: * See attached FSA Bid and Spec sheets

Quoted prices do not include Federal, State or Local taxes which may be applicable. Quoted prices include normal testing, packaging and instructional literature. Special testing, packaging, additional instructional literature, parts, provisioning lists or prints are not included, and prices will be quoted separately.

Quotation Firm for 30 Day(s) Delivery Notes: 12-14 Weeks

BY: _____ goe Antonini_

Joe Antonini Mid Florida Diesel, Inc.